



Coil Klean

CK20

SDS Revision Date (mm/dd/yyyy): 05/14/2015

Page 1 of 11

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Coil Klean**

Product Code(s) : CK20 (P/N 475252)

Recommended use of the chemical and restrictions on use

: Professional Use Only: Refrigeration coil cleaner

Chemical family : Mixture.

Name, address, and telephone number of the supplier:

Parker Hannifin Corporation - Sporlan Division

206 Lange Drive
Washington, MO, U.S.A.
63090

Supplier's Telephone # : (636)-239-1111

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887 (Outside U.S.).

Name, address, and telephone number of the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

WHMIS information: This product is a WHMIS Controlled Product. It meets one or more of the criteria for a controlled product provided in Part IV of the Canadian Controlled Products Regulations (CPR). WHMIS classification:
Class A (Pressurized containers)
Class D2B (Materials Causing Other Toxic Effects, Toxic Material)

OSHA: This material is classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012).
OSHA Classification:

Flammable Aerosols - Category 2
Gases under pressure - Liquefied gas
Eye Damage/Irritation - Category 2A
Skin corrosion/irritation Skin Irritation - Category 2

Label elements

The following label information is applicable only to the United States according to OSHA Regulations (29 CFR 1910.1200) (Hazcom 2012):

Signal Word

WARNING!

Hazard statement(s)

Flammable aerosol.
Contains gas under pressure; may explode if heated.
Causes skin irritation.
Causes serious eye irritation.



Coil Klean

CK20

SDS Revision Date (mm/dd/yyyy): 05/14/2015

Page 2 of 11

SAFETY DATA SHEET

Precautionary statement(s)

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
Do not spray on an open flame or other ignition source.
Pressurized container: Do not pierce or burn, even after use.
Wash thoroughly after handling.
Wear protective gloves and eye/face protection.

IF ON SKIN: Wash with plenty of soap and water.
If skin irritation occurs, get medical advice/attention.
Take off contaminated clothing and wash it before reuse.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists, get medical advice/attention.

Protect from sunlight. Do not expose to temperatures exceeding 50°C/122°F. Store in a well-ventilated place.



The following label information is applicable only to Canada according to the Canadian Controlled Products Regulations (CPR/WHMIS):

DANGER!

Flammable aerosol. Gas Under Pressure Do not puncture, incinerate or expose to heat even when empty. Causes skin and eye irritation.

Use in a well-ventilated area. Wear protective gloves/clothing and eye/face protection. Do not ingest. Do not breathe vapours or spray mist. Keep away from bases, metals and other incompatibles. Keep away from incompatibles. Keep containers tightly closed when not in use. Wash thoroughly after handling.

IF INHALED: Remove person to fresh air and keep comfortable for breathing. If breathing stopped, begin artificial respiration. If breathing is difficult, administer oxygen. IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower. Immediately call a POISON CENTRE or doctor/physician.



Other hazards

Other hazards which do not result in classification:

Ingestion may cause severe irritation to the mouth, throat and stomach. Prolonged skin contact may cause dermatitis (rash), characterized by red, dry, itching skin. May cause respiratory tract irritation. Contact with liquid or refrigerated gas can cause cold burns and frostbite.



Coil Klean

CK20

SDS Revision Date (mm/dd/yyyy): 05/14/2015

Page 3 of 11

SAFETY DATA SHEET

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u>	<u>CAS #</u>	<u>Concentration</u>
1-Propoxy-2-propanol	1569-01-3	5.0 - 10.0
Trisodium phosphate	7601-54-9	1.0 - 5.0
Butane	106-97-8	1.0 - 5.0
Propane	74-98-6	1.0 - 5.0
Sodium metasilicate	6834-92-0	1.0 - 5.0

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : Do NOT induce vomiting. Have victim rinse mouth with water, then give one to two glasses of water to drink. Seek immediate medical attention/advice. Never give anything by mouth if victim is unconscious.
- Inhalation* : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.
- Skin contact* : Take off all contaminated clothing immediately. For skin contact, flush with water for at least 15 minutes, while removing contaminated clothing. Do not rub area of contact. Seek immediate medical attention/advice. Wash contaminated clothing before reuse.
- Eye contact* : For eye contact, flush with running water for at least 15 minutes. Seek immediate medical attention/advice.

Most important symptoms and effects, both acute and delayed

- : Causes skin irritation. Symptoms may include redness, itching and swelling. Causes serious eye irritation. Symptoms may include stinging and tearing. Contact with liquid or refrigerated gas can cause cold burns and frostbite. May cause respiratory irritation. In high concentrations, symptoms may include sore throat, sneezing, coughing and shortness of breath. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Inhaling high concentrations may cause central nervous system depression, with effects ranging from dizziness and headache to unconsciousness.

Indication of any immediate medical attention and special treatment needed

- : Immediate medical attention is required. Causes burns. Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

- Suitable extinguishing media*
- : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment. Water spray may be used to cool closed containers to prevent pressure build-up and possible autoignition or explosion when exposed to extreme heat.

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Flammable aerosol Contents under pressure. Do not pierce or burn, even after use. Do not spray on a naked flame or any incandescent material.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable Aerosols - Category 2

Explosion Data: Sensitivity to Mechanical Impact / Static Discharge:

- : Aerosols are sensitive to mechanical impact.

Hazardous combustion products

- : Oxides of phosphorus. Carbon dioxide and carbon monoxide.

Special protective equipment and precautions for firefighters



Coil Klean

CK20

SDS Revision Date (mm/dd/yyyy): 05/14/2015

Page 4 of 11

SAFETY DATA SHEET

Protective equipment for fire-fighters

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Special fire-fighting procedures

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode. A full-body chemical resistant suit should be worn. Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Dike for water control. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : All persons dealing with clean-up should wear the appropriate protective equipment including self-contained breathing apparatus. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION, for additional information on acceptable personal protective equipment.

Environmental precautions

- : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up

- : Remove all sources of ignition. Ventilate area of release. Stop spill or leak at source if safely possible. Dike for water control. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Contact the proper local authorities.

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): (100 lbs / 45.4 kg) disodium metasilicate

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Use in a well-ventilated area. Wear protective gloves and eye/face protection. See Section 8 for additional personal protection advice when handling this product. Do not ingest. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Keep away from extreme heat and flame. Keep away from bases, metals and other incompatibles. Keep container tightly closed when not in use. Wash thoroughly after handling. Do not puncture, incinerate or expose to heat even when empty.

Conditions for safe storage

- : Store in a cool, dry, well-ventilated area. Store away from incompatibles and out of direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. Protect from sunlight and do not expose to temperatures exceeding 50 °C/122 °F.

Incompatible materials

- : Oxidizing agents

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION



Coil Klean

CK20

SDS Revision Date (mm/dd/yyyy): 05/14/2015

Page 5 of 11

SAFETY DATA SHEET

<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
1-Propoxy-2-propanol	N/Av	N/Av	N/Av	N/Av
Trisodium phosphate	N/Av	N/Av	N/Av	N/Av
Butane	1000 ppm (Butane, all isomers)	N/Av	800 ppm (final rule limit)	N/Av
Propane	N/Av	N/Av	1000 ppm (1800 mg/m ³)	N/Av
Sodium metasilicate	N/Av	N/Av	N/Av	N/Av

Exposure controls

Ventilation and engineering measures

: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Respiratory protection

: If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Confirmation of which type of respirator is most suitable for the intended application should be obtained from respiratory protection suppliers. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection

: Wear chemically protective gloves (impervious), boots, aprons, and gauntlets to prevent prolonged or repeated skin contact. Wear impervious gloves, such as butyl rubber. Unsuitable material: polyvinyl alcohol. Advice should be sought from glove suppliers.

Eye / face protection

: Tightly fitting safety goggles

Other protective equipment

: Other equipment may be required depending on workplace standards. An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

: Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Do not eat, drink, smoke or use cosmetics while working with this product. Upon completion of work, wash hands before eating, drinking, smoking or use of toilet facilities. Remove and wash contaminated clothing before re-use. Do not take contaminated clothing home.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid contained in a pressurized, aerosol can.

Odour : Characteristic odor.

Odour threshold : N/Av

pH : Not available.

Melting/Freezing point : Not available.

Initial boiling point and boiling range

: Not available.

Flash point : Not available.

Flashpoint (Method) : Not applicable.

Evaporation rate (BuAe = 1) : >1

Flammability (solid, gas) : Flammable aerosols are not also classified as flammable gases.

Lower flammable limit (% by vol.) : N/Av

Upper flammable limit (% by vol.) : N/Av



Coil Klean

CK20

SDS Revision Date (mm/dd/yyyy): 05/14/2015

Page 6 of 11

SAFETY DATA SHEET

Oxidizing properties : None known.
Explosive properties : Aerosols are sensitive to mechanical impact.
Vapour pressure : Not available.
Vapour density : Not available.
Relative density / Specific gravity
: 1.05
Solubility in water : soluble
Other solubility(ies) : None known.
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution
: 2.89
Auto-ignition temperature : N/Ap
Decomposition temperature : Not available.
Viscosity : Not available.
Volatiles (% by weight) : Not available.
Volatile organic Compounds (VOC's)
: Not available.
Absolute pressure of container
: N/Ap
Flame projection length : N/Ap
Other physical/chemical comments
: Heat of combustion: 4.23 kJ/g

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under the recommended storage and handling conditions prescribed.
Possibility of hazardous reactions
: Hazardous polymerization does not occur.
Conditions to avoid : Avoid heat and open flame. Ensure adequate ventilation, especially in confined areas.
Avoid contact with incompatible materials. Keep out of direct sunlight.
Incompatible materials : Oxidizing agents
Hazardous decomposition products
: Refer also to hazardous combustion products, Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption
: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: May cause respiratory irritation. Symptoms may include coughing, choking and wheezing. Inhalation of high concentrations may cause dizziness, disorientation, incoordination, narcosis, nausea or narcotic effects.



Coil Klean

CK20

SDS Revision Date (mm/dd/yyyy): 05/14/2015

Page 7 of 11

SAFETY DATA SHEET

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin

: Causes skin irritation. Symptoms may include redness, itching and swelling. Contact may cause frostbite. If product is directly applied to the skin, symptoms of frostbite may be experienced including numbness, prickling and itching.

Sign and symptoms eyes

: Causes serious eye irritation. Symptoms may include tearing, redness and discomfort. Contact may cause frostbite. If product is sprayed directly into the eyes, could cause freezing of the eye.

Potential Chronic Health Effects

: Chronic skin contact with low concentrations may cause dermatitis.

Mutagenicity

: Not expected to be mutagenic in humans.

Carcinogenicity

: No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

: Not expected to cause reproductive effects.

Senitization to material

: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

: The substance or mixture is not classified as specific target organ toxicant, single exposure.
 The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Irritancy

: Causes skin irritation. Causes eye irritation.

Medical conditions aggravated by overexposure

: Pre-existing skin, eye and respiratory disorders.

Synergistic materials

: Not available.

Toxicological data

: The calculated ATE values for this mixture are:
 ATE oral = >5000 mg/kg

See below for individual ingredient acute toxicity data.

<u>Chemical name</u>	<u>LC₅₀(4hr)</u> <u>inh, rat</u>	<u>LD₅₀</u>	
		<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
1-Propoxy-2-propanol	N/Av	2504 mg/kg	N/Av
Trisodium phosphate	>2.16 mg/L 1 h	>2000 mg/kg	N/Av
Butane	276 000 ppm	N/Av (gas)	N/Av (gas)
Propane	N/Av	N/Av (gas)	N/Av (gas)
Sodium metasilicate	N/Av	600 mg/kg	>4640 mg/kg

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. There is no data available for this product.

Ecotoxicity data:

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Fish</u>		
		<u>LC50 / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>



Coil Klean

CK20

SDS Revision Date (mm/dd/yyyy): 05/14/2015

Page 8 of 11

SAFETY DATA SHEET

<u>Ingredients</u>	CAS No	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor

<u>Ingredients</u>	CAS No	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor

Persistence and degradability

: No data is available on the product itself.

Bioaccumulation potential

: No data is available on the product itself.

Mobility in soil

: No data is available on the product itself.

Other Adverse Environmental effects

: No additional information.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle waste according to recommendations in Section 7. Empty containers retain residue (liquid and/or vapour) and can be dangerous. Do not puncture or incinerate containers.

Methods of Disposal

: Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORTATION INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1950	Aerosols, flammable	2.1	none	
49CFR/DOT Additional information	May be shipped as Limited Quantity when shipped per packing instruction Y203.				
TDG	UN1950	AEROSOLS, flammable	2.1	none	
TDG Additional information	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass.				
ICAO/IATA	UN1950	Aerosols, flammable	2	none	
ICAO/IATA Additional information	Refer to ICAO/IATA Packing Instruction				

Special precautions for user

: None known.

Environmental hazards

: See ECOLOGICAL INFORMATION, Section 12.



Coil Klean

CK20

SDS Revision Date (mm/dd/yyyy): 05/14/2015

Page 9 of 11

SAFETY DATA SHEET

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: Not applicable.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

Ingredients	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
1-Propoxy-2-propanol	1569-01-3	Yes	N/Ap	N/Av	No	N/Ap
Trisodium phosphate	7601-54-9	Yes	5000 lb final RQ (listed under Sodium phosphate, tribasic); 2270 kg final RQ (listed under Sodium phosphate, tribasic)	N/Av	No	N/Ap
Butane	106-97-8	Yes	N/Ap	N/Av	No	N/Ap
Propane	74-98-6	Yes	None.	None.	No	N/Ap
Sodium metasilicate	6834-92-0	Yes	N/Ap	N/Av	No	N/Ap

SARA TITLE III: Sec. 311 and 312, MSDS Requirements, 40 CFR 370 Hazard Classes: Acute Health Hazard; Fire Hazard .Pressurized gas hazard Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

Ingredients	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
1-Propoxy-2-propanol	1569-01-3	No	N/Ap	No	No	No	No	No	No
Trisodium phosphate	7601-54-9	No	N/Ap	Yes	Yes	Yes	Yes	Yes	No
Butane	106-97-8	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes
Propane	74-98-6	No	N/Ap	No	Yes	Yes	Yes	Yes	Yes
Sodium metasilicate	6834-92-0	No	N/Ap	No	No	No	No	No	No

40CFR Protection of Environment; Part 82 Protection of Stratospheric Ozone - CAA Section 602, Class I Substance.

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

This product has been classified according to the hazard criteria of the CPR and the MSDS contains all of the information required by the CPR.



Coil Klean

CK20

SDS Revision Date (mm/dd/yyyy): 05/14/2015

Page 10 of 11

SAFETY DATA SHEET

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	<u>CAS #</u>	<u>European EINECs</u>	<u>Australia AICS</u>	<u>Philippines PICCS</u>	<u>Japan ENCS</u>	<u>Korea KECI/KECL</u>	<u>China IECSC</u>	<u>NewZealand IOC</u>
1-Propoxy-2-propanol	1569-01-3	216-372-4	Present	Present	(7)-97	KE-29773	Present	HSR001420
Trisodium phosphate	7601-54-9	231-509-8	Present	Present	(1)-497	KE-34912	Present	HSR002736
Butane	106-97-8	203-448-7	Present	Present	(2)-4	KE-03751	Present	HSR000989
Propane	74-98-6	200-827-9	Present	Present	(2)-3	KE-29258	Present	HSR001010
Sodium metasilicate	6834-92-0	229-912-9	Present	Present	(1)-508	KE-12354	Present	HSR003511

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
CA: California
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
DOT: Department of Transportation
EPA: Environmental Protection Agency
HMIS: Hazardous Materials Identification System
HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
Inh: Inhalation
IUCLID: International Uniform Chemical Information Database
MA: Massachusetts
MN: Minnesota
MSHA: Mine Safety and Health Administration
N/Av: Not Applicable
N/Av: Not Available
NFPA: National Fire Protection Association
NIOSH: National Institute of Occupational Safety and Health
NJ: New Jersey
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
RCRA: Resource Conservation and Recovery Act
RI: Rhode Island
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

References

: Canadian Centre for Occupational Health and Safety, CCHInfoWeb Databases, 2015 (Chempendium, RTECs, HSDB, INCHEM).
European Chemicals Agency, Classification Legislation, 2015
Material Safety Data Sheet from manufacturer
OECD- The Global Portal to Information on Chemical Substances - eChemPortal, 2015

Preparation Date (mm/dd/yyyy)

: 05/14/2015



Coil Klean

CK20

SDS Revision Date (mm/dd/yyyy): 05/14/2015

Page 11 of 11

SAFETY DATA SHEET

Reviewed Date SDS (dd/mm/yyyy)

: 14/05/2015

Revision No.

: 2

Revision Information

: All (format change)

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

HMIS Rating



: * - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: 2 *Flammability:* 0 *Reactivity:* 0

NFPA Rating

0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

: *Health:* 2 *Flammability:* 0 *Instability:* 0 *Special Hazards:* None.

<p><u>Prepared for:</u> Parker Hannifin Corporation - Sporlan Division 206 Lange Drive, Washington, MO, U.S.A. 63090 Telephone: (636) 239-1111 www.parker.com Direct all enquiries to: Parker Hannifin Corp. - Sporlan Division.</p>	
<p><u>Prepared by:</u> ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.); (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	

DISCLAIMER

This Material Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by / obtained from Parker Hannifin Corp and CCOHS' Web Information Service. The information in the Material Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Parker Hannifin Corp expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this MSDS does not apply to use with any other product or in any other process.

This Material Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Parker Hannifin Corp.

END OF DOCUMENT