

Parker Hannifin Corporation - Sporlan Division 206 Lange Drive Washington, MO, U.S.A., 63090 Telephone: (636) 239 1111



Guardian VG-3 Refridgeration Oil

VG-3 MO -Q, VG-3 MO -1, VG-3 MO-5, VG-3 MO-55

SDS Preparation Date (mm/dd/yyyy): 04/27/2016

Page 1 of 9

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

Guardian VG-3 Refridgeration Oil

Product Code(s) : VG-3 MO -Q, VG-3 MO -1, VG-3 MO-5, VG-3 MO-55

Recommended use of the chemical and restrictions on use

Use pattern: Professional Use Only Restriction on use: None known

Chemical family : Petroleum hydrocarbon

Name, address, and telephone number

of the supplier:

Name, address, and telephone number of

the manufacturer:

Parker Hannifin Corporation - Sporlan Division

Refer to supplier

206 Lange Drive

Washington, MO, U.S.A.

63090

Supplier's Telephone #

: (636) 239-1111

24 Hr. Emergency Tel#

Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887

(Outside U.S.).

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear to light yellow. Mild petroleum odour.

This material is not classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Label elements

Signal Word

Not required

Hazard statement(s)

None required.

Precautionary statement(s)

None required.

Other hazards

Other hazards which do not result in classification: May cause slight eye and skin irritation. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture

Chemical name	Common name and synonyms	CAS#	Concentration (% by weight)
Distillates (petroleum), hydrotreated heavy naphthenic	Distillates, petroleum, hydrotreated heavy naphthenic	64742-52-5	>90
Additives	Not available.	Proprietary	Proprietary



Parker Hannifin Corporation - Sporlan Division 206 Lange Drive

> Washington, MO, U.S.A., 63090 Telephone: (636) 239 1111

Guardian VG-3 Refridgeration Oil

VG-3 MO -Q, VG-3 MO -1, VG-3 MO-5, VG-3 MO-55

SDS Preparation Date (mm/dd/yyyy): 04/27/2016

Page 2 of 9

SAFETY DATA SHEET

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

Ingestion

: Do NOT induce vomiting. Never give anything by mouth to an unconscious person.

Get medical attention if symptoms persist.

Inhalation

Move to fresh air. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing has stopped, give artificial respiration. If irritation or symptoms

develop, seek medical attention.

Skin contact

: For skin contact, wash with soap and water while removing contaminated clothing. If irritation persists, seek prompt medical attention. Wash contaminated clothing before

Eve contact

: Immediately flush eyes with running water for at least 5 to 10 minutes. If irritation

persists, seek prompt medical attention.

Most important symptoms and effects, both acute and delayed

: May be mildly irritating to eyes and skin. Symptoms may include mild redness and swelling. Oils can block the skin pores causing an acne-like disorder. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May cause irritation of respiratory tract. Symptoms may include sore throat, running nose and shortness of breath.

Indication of any immediate medical attention and special treatment needed

: Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

: Use media suitable to the surrounding fire such as water fog or fine spray, alcohol foams, carbon dioxide and dry chemical.

Unsuitable extinguishing media

: Do not use water jet, as this may spread burning material.

Special hazards arising from the substance or mixture / Conditions of flammability

: Not flammable under normal conditions of use. However, may ignite if exposed to extreme heat and flame. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

: Non-flammable.

Hazardous combustion products

: Nitrogen oxides (NOx) ;Carbon oxides ;Sulfur oxides ;Phosphorus oxides ;Zinc oxide

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

: Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures

: Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame. Prevent fire extinguishing water from contaminating surface water or the ground water system. Dike for water control.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

: Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Refer to protective measures listed in sections 7 and 8.

Environmental precautions: Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.



Parker Hannifin Corporation - Sporlan Division 206 Lange Drive

> Washington, MO, U.S.A., 63090 Telephone: (636) 239 1111

Guardian VG-3 Refridgeration Oil

VG-3 MO -Q, VG-3 MO -1, VG-3 MO-5, VG-3 MO-55

SDS Preparation Date (mm/dd/yyyy): 04/27/2016

Page 3 of 9

SAFETY DATA SHEET

Methods and material for containment and cleaning up

: Remove all sources of ignition. Ventilate area of release. Stop the spill at source if it is safe to do so. Dike for water control. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as required. Refer to Section 13 for disposal of contaminated material.

Special spill response procedures

: If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).

US CERCLA Reportable quantity (RQ): None.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

Wear suitable protective equipment during handling. Use with adequate ventilation. Avoid breathing fumes or mists. Use non-sparking tools. Keep away from extreme heat and flame. Avoid contact with incompatible materials. Keep containers closed when not in use. Wash thoroughly after handling. Bond and ground transfer containers

and equipment to avoid static accumulation.

Conditions for safe storage

Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Inspect periodically for damage or leaks. Protect against physical damage. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel.

Incompatible materials

: Oxidizing agents.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:								
Chemical Name	ACGIH	TLV	OSHA F	<u>PEL</u>				
	<u>TWA</u>	STEL	PEL	<u>STEL</u>				
Distillates (petroleum), hydrotreated heavy naphthenic	5 mg/m³ (As 'Oil mist, mineral')	N/Av	5 mg/m³ (As 'Oil mist, mineral')	N/Av				
Additives	N/Av	N/Av	N/Av	N/Av				

Exposure controls

Ventilation and engineering measures

: Use with adequate ventilation. Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits. Use explosion-proof electrical and ventilating equipment.

Respiratory protection

: If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Advice should be sought from respiratory protection specialists.

Skin protection

Gloves impervious to the material are recommended. Advice should be sought from glove suppliers.

Eye / face protection

: Safety goggles or glasses as appropriate for the job.

Other protective equipment : Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. Ensure that eyewash stations and safety showers are close to the workstation location.

General hygiene considerations

Avoid breathing fumes or mists. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use.



Telephone: (636) 239 1111

Guardian VG-3 Refridgeration Oil

VG-3 MO -Q, VG-3 MO -1, VG-3 MO-5, VG-3 MO-55

SDS Preparation Date (mm/dd/yyyy): 04/27/2016

Page 4 of 9

SAFETY DATA SHEET

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Clear to yellow liquid.

Odour : Petroleum odor.

Odour threshold : N/Av
pH : N/Av
Melting/Freezing point : N/Av
Initial boiling point and boiling range

: >230°C (446°F)

Flash point : >225°C (437°F)

Flashpoint (Method) : Pensky Martens Closed Cup

Evaporation rate (BuAe = 1) : N/Av

Flammability (solid, gas) : Not flammable.

Lower flammable limit (% by vol.)

: N/Av

Upper flammable limit (% by vol.)

: N/Av

Oxidizing properties: None known.Explosive properties: Not explosiveVapour pressure: <0.1 mmHg</th>

Vapour density : > Relative density / Specific gravity

: 0.84-0.87

Solubility in water : insoluble Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: >20

Auto-ignition temperature : N/Av **Decomposition temperature** : N/Av

Viscosity : >20.6 cSt - 320 cSt @ 40°C

Volatiles (% by weight) : Nil Volatile organic Compounds (VOC's)

: N/Av

Absolute pressure of container

: N/Ap : N/Ap

Flame projection length : N/Ap Other physical/chemical comments

: None known or reported by the manufacturer.

SECTION 10. STABILITY AND REACTIVITY

Reactivity: Not normally reactive.

Chemical stability : Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

: Hazardous polymerization will not occur.

Conditions to avoid : Avoid heat and open flame. Avoid contact with incompatible materials. Do not use in

areas without adequate ventilation.

Incompatible materials : See Section 7 (Handling and Storage) for further details.

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.



Parker Hannifin Corporation - Sporlan Division 206 Lange Drive

Washington, MO, U.S.A., 63090 Telephone: (636) 239 1111

Guardian VG-3 Refridgeration Oil

VG-3 MO -Q, VG-3 MO -1, VG-3 MO-5, VG-3 MO-55

SDS Preparation Date (mm/dd/yyyy): 04/27/2016

Page 5 of 9

SAFETY DATA SHEET

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption

: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: If product is heated or mists are formed, inhalation may cause irritation to the nose,

throat and respiratory tract.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May

cause irritation of mouth, throat, and stomach.

Sign and symptoms skin : Direct skin contact may cause slight or mild, transient irritation.

Sign and symptoms eyes : May cause mild irritation, redness and watering.

Potential Chronic Health Effects

: Oils can block the skin pores causing an acne-like disorder.

Mutagenicity : Not expected to be mutagenic in humans.

Carcinogenicity : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

: Not expected to cause reproductive effects.

Sensitization to material: Not expected to be a skin or respiratory sensitizer.

Specific target organ effects: This material is not classified as hazardous under U.S. OSHA regulations (29CFR

1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products

Regulations) (WHMIS 2015).

Medical conditions aggravated by overexposure

: Pre-existing skin and respiratory disorders.

Synergistic materials : Not available.

Toxicological data : See below for toxicological data on the substance.

	LCso(4hr)	LD ₅₀			
Chemical name	inh, rat	(Oral, rat)	(Rabbit, dermal)		
Distillates (petroleum), hydrotreated heavy naphthenic	> 5 mg/L (mist)	> 5000 mg/kg	> 2000 mg/kg		
Additives	N/Av	N/Av	N/Av		

Other important toxicological hazards

: None known or reported by the manufacturer.



Telephone: (636) 239 1111

Guardian VG-3 Refridgeration Oil

VG-3 MO -Q, VG-3 MO -1, VG-3 MO-5, VG-3 MO-55

SDS Preparation Date (mm/dd/yyyy): 04/27/2016

Page 6 of 9

SAFETY DATA SHEET

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

: Not expected to be harmful to aquatic organisms. However, this does not exclude the possibility that large or frequent spills can have a harmful or damaging effect on the environment. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

lucus di cuto	040 N-	Toxicity to Fish				
<u>Ingredients</u>	CAS No	LC50 / 96h	NOEC / 21 day	M Factor		
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 5000 mg/L (Rainbow trout)	N/Av	None.		
Additives	Proprietary	N/Av	N/Av	N/Av		

<u>Ingredients</u>	CAS No	Toxi	Toxicity to Daphnia			
		EC50 / 48h	NOEC / 21 day	M Factor		
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 1000 mg/L (Daphnia magna)	N/Av	None.		
Additives	Proprietary	N/Av	N/Av	N/Av		

<u>Ingredients</u>	CAS No	Toxicity to Algae				
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor		
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	> 1000 mg/L/96hr (Green algae)	N/Av	None.		
Additives	Proprietary	N/Av	N/Av	N/Av		

Persistence and degradability

: Inherently biodegradable.

Bioaccumulation potential: The product itself has not been tested.

<u>Components</u>	Partition coefficient n-octanol/water (log Kow)	Bioconcentration factor (BCF)
Distillates (petroleum), hydrotreated heavy naphthenic (CAS 64742-52-5)	>20	N/Av
Additives (CAS Proprietary)	N/Av	N/Av

Mobility in soil : The product itself has not been tested.

Other Adverse Environmental effects

: None known.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal Methods of Disposal : Handle waste according to recommendations in Section 7.

 Dispose in accordance with all applicable federal, state, provincial and local regulations.



Telephone: (636) 239 1111

Guardian VG-3 Refridgeration Oil

VG-3 MO -Q, VG-3 MO -1, VG-3 MO-5, VG-3 MO-55

SDS Preparation Date (mm/dd/yyyy): 04/27/2016

Page 7 of 9

SAFETY DATA SHEET

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label	
49CFR/DOT	None.	Not regulated.	Not regulated	none	\otimes	
49CFR/DOT Additional information	None.		:			
TDG	None.	Not regulated.	Not regulated	none	\otimes	
TDG Additional information	None.		ļ			
ICAO/IATA	None.	Not regulated.	Not regulated	none	\otimes	
ICAO/IATA Additional information	None.	!	ļ			

Special precautions for user: Appropriate advice on safety must accompany the package.

Environmental hazards : This substance does not meet the criteria for an environmentally hazardous substance

according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: This information is not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

La maradia mata		TSCA	CERCLA Reportable	SARA TITLE III: Sec. 302, Extremely	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical		
<u>Ingredients</u>	CAS#	Quantity(RQ) (40 Substand	Hazardous Substance, 40 CFR 355:	Toxic Chemical de min Concent			
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	Yes	N/Ap	N/Av	No	0.1%	
Additives	Proprietary	NS	None.	None.	No	N/Ap	

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: None.

Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds for the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.



Parker Hannifin Corporation - Sporlan Division 206 Lange Drive

Washington, MO, U.S.A., 63090 Telephone: (636) 239 1111

Guardian VG-3 Refridgeration Oil

VG-3 MO -Q, VG-3 MO -1, VG-3 MO-5, VG-3 MO-55

SDS Preparation Date (mm/dd/yyyy): 04/27/2016

Page 8 of 9

SAFETY DATA SHEET

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS#	CAS# California		State "Right to Know" Lists					
	OAO II	Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	No	N/Ap	No	No	No	No	No	No
Additives	Proprietary	No	N/Ap	No	No	No	No	No	No

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS#	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Distillates (petroleum), hydrotreated heavy naphthenic	64742-52-5	265-155-0	Present	Present	(9)-1689	KE-12543	Present	No information available.
Additives	Proprietary	N/Av	N/Av	N/Av	N/Av	N/Av	N/Av	N/Av

SECTION 16. OTHER INFORMATION

Legend

ACGIH: American Conference of Governmental Industrial Hygienists

CA: California

CAS: Chemical Abstract Services

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

of 1980

CFR: Code of Federal Regulations DOT: Department of Transportation EPA: Environmental Protection Agency

HMIS: Hazardous Materials Identification System HSDB: Hazardous Substances Data Bank

IARC: International Agency for Research on Cancer

Inh: Inhalation

IUCLID: International Uniform Chemical Information Database

MA: Massachusetts MN: Minnesota

mppcf: million particles per cubic foot

MSHA: Mine Safety and Health Administration

N/Ap: Not Applicable N/Av: Not Available

NFPA: National Fire Protection Association

NIOSH: National Institute of Occupational Safety and Health

NJ: New Jersey

NTP: National Toxicology Program



Telephone: (636) 239 1111

Guardian VG-3 Refridgeration Oil

VG-3 MO -Q, VG-3 MO -1, VG-3 MO-5, VG-3 MO-55

SDS Preparation Date (mm/dd/yyyy): 04/27/2016

Page 9 of 9

SAFETY DATA SHEET

OSHA: Occupational Safety and Health Administration

PA: Pennsylvania

PEL: Permissible exposure limit

RCRA: Resource Conservation and Recovery Act

RI: Rhode Island

RTECS: Registry of Toxic Effects of Chemical Substances SARA: Superfund Amendments and Reauthorization Act

STEL: Short Term Exposure Limit

TDG: Canadian Transportation of Dangerous Goods Act & Regulations

TLV: Threshold Limit Values TWA: Time Weighted Average

WHMIS: Workplace Hazardous Materials Identification System

References : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents &

Biological Exposure Indices for 2016.

2. International Agency for Research on Cancer Monographs, searched 2016.

3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2016

(Chempendium, HSDB and RTECs).

Material Safety Data Sheets from manufacturer.
 US EPA Title III List of Lists - 2016 version.

6. California Proposition 65 List

Preparation Date (mm/dd/yyyy)

: 04/27/2016

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

HMIS Rating : *- Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

Health: 1 Flammability: 0 Reactivity: 0

NFPA Rating 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe

: Health: 1 Flammability0 Instability:0 Special Hazards: None.

Prepared for:

Parker Hannifin Corporation Sporlan Division 206 Lange Drive, Washington, MO 63090 U.S.A.

Telephone: (636) 239-1111

www.parker.com

Direct all enquiries to: Parker Hannifin Corp. Sporlan

Division.

Prepared by:

ICC The Compliance Center Inc.

Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)

http://www.thecompliancecenter.com



DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Parker Hannifin Corporation and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Parker Hannifin Corporation expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Parker Hannifin Corporation.