



Parker Hannifin Corporation - Sporlan Division
206 Lange Drive
Washington, MO, U.S.A., 63090
Telephone: (636) 239 1111

Premium Elastic Sealant Compound

PP22 (P/N 475296)

SDS Revision Date (mm/dd/yyyy): 02/06/2019

Page 1 of 10

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Premium Elastic Sealant Compound**

Product Code(s) : PP22 (P/N 475296)

Recommended use of the chemical and restrictions on use

: Air conditioning and refrigeration sealer slugs for sealing around components.
Restriction on use: None known

Chemical family : Mixture.

Name, address, and telephone number
of the supplier:

Parker Hannifin Corporation - Sporlan Division

206 Lange Drive
Washington, MO, U.S.A.
63090

Supplier's Telephone # : (636) 239-1111

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887
(Outside U.S.).

Name, address, and telephone number of
the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Tacky, off-white, gray, non-hardening sealing compound (rubber-like).

This material is not classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015).

Label elements

Hazard pictogram(s)

None required under U.S. OSHA Hazcom 2012 and Canadian WHMIS 2015 regulations.

Signal Word

Not required

Hazard statement(s)

None required.

Precautionary statement(s)

None required.

Other hazards

Other hazards which do not result in classification:

Toxic fumes may be released during a fire. May form combustible dust concentrations in air (during processing). May be mildly irritating to eyes and skin. Fumes from heated product may irritate respiratory tract. If dusts are formed, inhalation may cause adverse lung effects.

Environmental precautions: Avoid release to the environment. See ECOLOGICAL INFORMATION, Section 12.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
----------------------	---------------------------------	--------------	------------------------------------



Premium Elastic Sealant Compound

PP22 (P/N 475296)

SDS Revision Date (mm/dd/yyyy): 02/06/2019

Page 2 of 10

SAFETY DATA SHEET

Calcium carbonate	Calcite	1317-65-3	60.0 - 80.0
talc	Talcum	14807-96-6	3.0 - 7.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Get medical attention if symptoms persist.
- Inhalation* : Move to fresh air. If breathing is difficult, give oxygen by qualified medical personnel only. If breathing has stopped, give artificial respiration. If irritation or symptoms develop, seek medical attention.
- Skin contact* : IF ON SKIN: Wash with plenty of soap and water. If irritation persists, seek prompt medical attention. Wash contaminated clothing before reuse.
- Eye contact* : IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If irritation persists, seek prompt medical attention.

Most important symptoms and effects, both acute and delayed

- : May be mildly irritating to eyes and skin. Fumes from heated product may irritate respiratory tract. If dusts are formed, inhalation may cause adverse lung effects.

Indication of any immediate medical attention and special treatment needed

- : Treat symptomatically.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Use media suitable to the surrounding fire such as water fog or fine spray, alcohol foams, carbon dioxide and dry chemical.

Unsuitable extinguishing media

- : Do not use water jet, as this may spread burning material.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Not flammable under normal conditions of use. However, may ignite if exposed to extreme heat and flame. Closed containers may rupture if exposed to excess heat or flame due to a build-up of internal pressure.

Flammability classification (OSHA 29 CFR 1910.106)

- : Non-flammable.

Hazardous combustion products

- : Carbon oxides; Calcium oxides; Nitrogen oxides (NOx); Sulphur oxides; Phosphorus oxides; Polycyclic aromatic hydrocarbons; formaldehyde; Other unidentified organic compounds.

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters should wear proper protective equipment and self-contained breathing apparatus with full face piece operated in positive pressure mode.

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : Restrict access to area until completion of clean-up. Ensure clean-up is conducted by trained personnel only. All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Refer to protective measures listed in sections 7 and 8.



Premium Elastic Sealant Compound

PP22 (P/N 475296)

SDS Revision Date (mm/dd/yyyy): 02/06/2019

Page 3 of 10

SAFETY DATA SHEET

Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces.

Methods and material for containment and cleaning up

- : Ventilate area of release. Stop the spill at source if it is safe to do so. Use inert, non-combustible absorbents to assist the pick up of material. Scrape up product and place it into a container for disposal. Notify the appropriate authorities as required. Refer to Section 13 for disposal of contaminated material.

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the national response center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): None.

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Wear suitable protective equipment during handling. Use with adequate ventilation. Training the workers on the potential health hazards associated with product vapor, dust or fume is important. Secondary inhalation exposures could occur when cleaning equipment, or when removing or laundering the clothing. Avoid breathing vapors, fumes or dust. Avoid contact with skin, eyes and clothing. Keep away from extreme heat and flame. Keep away from acids and incompatibles. Keep containers closed when not in use. Wash thoroughly after handling.

Conditions for safe storage : Keep containers tightly closed in a cool, well-ventilated place. Keep away from heat. Inspect periodically for damage or leaks. Protect against physical damage. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel.

Incompatible materials : Acids; Oxidizing agents.

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

<u>Exposure Limits:</u>				
<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Calcium carbonate	N/Av	N/Av	15 mg/m ³ (total dust); 5 mg/m ³ (respirable)	N/Av
talc	2 mg/m ³ (respirable)	N/Av	20 mppcf	N/Av

Exposure controls

Ventilation and engineering measures

- : Use with adequate ventilation. Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Respiratory protection : If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Advice should be sought from respiratory protection specialists.

Skin protection : Gloves impervious to the material are recommended. Advice should be sought from glove suppliers.

Eye / face protection : Safety goggles or glasses as appropriate for the job.

Other protective equipment : Where extensive exposure to product is possible, use resistant coveralls, apron and boots to prevent contact. Ensure that eyewash stations and safety showers are close to the workstation location.

General hygiene considerations



Premium Elastic Sealant Compound

PP22 (P/N 475296)

SDS Revision Date (mm/dd/yyyy): 02/06/2019

Page 4 of 10

SAFETY DATA SHEET

: Avoid breathing vapors, fumes or dust. Avoid contact with skin, eyes and clothing. Do not eat, drink or smoke when using this product. Wash thoroughly after handling. Remove and wash contaminated clothing before re-use.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Tacky, off-white, gray, non-hardening sealing compound (rubber-like).

Odour : No odour.

Odour threshold : N/Av

pH : N/Av

Melting/Freezing point : N/Av

Initial boiling point and boiling range

: N/Av

Flash point : N/Av

Flashpoint (Method) : N/Av

Evaporation rate (BuAe = 1) : N/Av

Flammability (solid, gas) : Not flammable.

Lower flammable limit (% by vol.)

: N/Av

Upper flammable limit (% by vol.)

: N/Av

Oxidizing properties : None known.

Explosive properties : Not explosive

Vapour pressure : N/Av

Vapour density : N/Av

Relative density / Specific gravity

: 1.6

Solubility in water : insoluble

Other solubility(ies) : N/Av

Partition coefficient: n-octanol/water or Coefficient of water/oil distribution

: N/Av

Auto-ignition temperature : N/Av

Decomposition temperature : N/Av

Viscosity : N/Av

Volatiles (% by weight) : N/Av

Volatile organic Compounds (VOC's)

: N/Av

Absolute pressure of container

: N/Av

Flame projection length : N/Av

Other physical/chemical comments

: No additional information.

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.

Chemical stability : Stable under the recommended storage and handling conditions prescribed.

Possibility of hazardous reactions

: Hazardous polymerization will not occur.

Conditions to avoid : Avoid heat and open flame. Avoid contact with incompatible materials. Do not use in areas without adequate ventilation.

Incompatible materials : Acids; Oxidizing agents.



Premium Elastic Sealant Compound

PP22 (P/N 475296)

SDS Revision Date (mm/dd/yyyy): 02/06/2019

Page 5 of 10

SAFETY DATA SHEET

Hazardous decomposition products

: None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES

Routes of entry skin & eye : YES

Routes of entry Ingestion : YES

Routes of exposure skin absorption
: NO

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

: Fumes from heated product may irritate respiratory tract. If dusts are formed, inhalation may cause adverse lung effects. High concentrations of dust may cause coughing and mild, temporary irritation.

Sign and symptoms ingestion

: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

Sign and symptoms skin

: Direct skin contact may cause slight or mild, transient irritation.

Sign and symptoms eyes

: May cause mild irritation, redness and watering.

Potential Chronic Health Effects

: None expected, when used as intended.
If dusts are formed, prolonged inhalation may result in chronic respiratory disease. Pneumoconiosis, or "dusty lung" disease, may result from chronic exposure to any dust.

Mutagenicity

: This product does not meet the criteria for germ cell mutagens under OSHA regulations (29 CFR 1910.1200) (Hazcom 2012) or WHMIS 2015.
No data available to indicate product or any components present at greater than 0.1% are mutagenic or genotoxic.

Carcinogenicity

: This product does not meet the criteria for carcinogens under OSHA regulations (29 CFR 1910.1200) (Hazcom 2012) or WHMIS 2015.
No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

: This material is not classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012) or WHMIS 2015.
This product is not expected to cause reproductive or developmental effects.

Sensitization to material

: This material is not classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012) or WHMIS 2015.
Not expected to be a skin or respiratory sensitizer.

Specific target organ effects : This material is not classified as hazardous under OSHA regulations (29CFR 1910.1200) (Hazcom 2012) or WHMIS 2015.

Medical conditions aggravated by overexposure

: Pre-existing skin and respiratory disorders.

Synergistic materials

: Not available.

Toxicological data

: No data is available on the product itself. See below for individual ingredient acute toxicity data. Contains no ingredients that are considered to have acute toxicity hazards.



Premium Elastic Sealant Compound

PP22 (P/N 475296)

SDS Revision Date (mm/dd/yyyy): 02/06/2019

Page 6 of 10

SAFETY DATA SHEET

<u>Chemical name</u>	<u>LC₅₀(4hr)</u>	<u>LD₅₀</u>	
	<u>inh, rat</u>	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Calcium carbonate	> 3 mg/L	6450 mg/kg	> 2000 mg/kg
talc	N/Av	N/Av	N/Av

Other important toxicological hazards

: None known or reported by the manufacturer.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity : No data is available on the product itself. The product should not be allowed to enter drains or water courses, or be deposited where it can affect ground or surface waters. See the following tables for individual ingredient ecotoxicity data.

Ecotoxicity data:

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Fish</u>		
		<u>LC50 / 96h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Calcium carbonate	1317-65-3	N/Av	N/Av	None.
talc	14807-96-6	N/Av	N/Av	None.

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Daphnia</u>		
		<u>EC50 / 48h</u>	<u>NOEC / 21 day</u>	<u>M Factor</u>
Calcium carbonate	1317-65-3	N/Av	N/Av	None.
talc	14807-96-6	N/Av	N/Av	None.

<u>Ingredients</u>	<u>CAS No</u>	<u>Toxicity to Algae</u>		
		<u>EC50 / 96h or 72h</u>	<u>NOEC / 96h or 72h</u>	<u>M Factor</u>
Calcium carbonate	1317-65-3	N/Av	N/Av	None.
talc	14807-96-6	N/Av	N/Av	None.

Persistence and degradability

: The product itself has not been tested.

Bioaccumulation potential

: The product itself has not been tested.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
talc (CAS 14807-96-6)		no known bioaccumulation

Mobility in soil : The product itself has not been tested.

Other Adverse Environmental effects

: None known.



Premium Elastic Sealant Compound

PP22 (P/N 475296)

SDS Revision Date (mm/dd/yyyy): 02/06/2019

Page 7 of 10

SAFETY DATA SHEET

SECTION 13. DISPOSAL CONSIDERATIONS

- Handling for Disposal** : Handle waste according to recommendations in Section 7.
- Methods of Disposal** : Dispose in accordance with all applicable federal, state, provincial and local regulations.
- RCRA** : If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	None.	Not regulated.	Not regulated	none	
49CFR/DOT Additional information	None.				
TDG	None.	Not regulated.	Not regulated	none	
TDG Additional information	None.				
ICAO/IATA	None.	Not regulated.	Not regulated	none	
ICAO/IATA Additional information	None.				

Special precautions for user : Appropriate advice on safety must accompany the package.

Environmental hazards : This substance does not meet the criteria for an environmentally hazardous substance according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

: This information is not available.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:



Premium Elastic Sealant Compound

PP22 (P/N 475296)

SDS Revision Date (mm/dd/yyyy): 02/06/2019

Page 8 of 10

SAFETY DATA SHEET

<u>Ingredients</u>	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de minimus Concentration
Calcium carbonate	1317-65-3	Yes	None.	None.	No	N/Ap
talc	14807-96-6	Yes	None.	None.	No	N/Ap

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: None. Under SARA Sections 311 and 312, the EPA has established threshold quantities for the reporting of hazardous chemicals. The current thresholds are 500 pounds or the threshold planning quantity (TPQ), whichever is lower, for extremely hazardous substances and 10,000 pounds for all other hazardous chemicals.

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Calcium carbonate	1317-65-3	No	N/Ap	No	Yes	Yes	Yes	Yes	Yes
talc	14807-96-6	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

WHMIS information: Refer to Section 2 for a WHMIS Classification for this product.

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS #	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	New Zealand IOC
Calcium carbonate	1317-65-3	215-279-6	Present	Present	(1)-122	KE-21996	Present	May be used as a single component chemical under an appropriate group standard.
talc	14807-96-6	238-877-9	Present	Present	(1)-468; (1)-468	KE-32773	Present	May be used as a single component chemical under an appropriate group standard.

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
CA: California



Premium Elastic Sealant Compound

PP22 (P/N 475296)

SDS Revision Date (mm/dd/yyyy): 02/06/2019

Page 9 of 10

SAFETY DATA SHEET

CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
DOT: Department of Transportation
EPA: Environmental Protection Agency
HMIS: Hazardous Materials Identification System
HSDB: Hazardous Substances Data Bank
IARC: International Agency for Research on Cancer
Inh: Inhalation
IUCID: International Uniform Chemical Information Database
MA: Massachusetts
MN: Minnesota
mppcf: million particles per cubic foot
MSHA: Mine Safety and Health Administration
N/Ap: Not Applicable
N/Av: Not Available
NFPA: National Fire Protection Association
NIOSH: National Institute of Occupational Safety and Health
NJ: New Jersey
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PA: Pennsylvania
PEL: Permissible exposure limit
RCRA: Resource Conservation and Recovery Act
RI: Rhode Island
RTECS: Registry of Toxic Effects of Chemical Substances
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TWA: Time Weighted Average
WHMIS: Workplace Hazardous Materials Identification System

- References** :
1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices for 2016
 2. International Agency for Research on Cancer Monographs, searched 2017
 3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases, 2017(Chempendium, HSDB and RTECs).
 4. Material Safety Data Sheets from manufacturer.
 5. US EPA Title III List of Lists - 2017 version.
 6. California Proposition 65 List - 2017 version.
 7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal, 2017.

Preparation Date (mm/dd/yyyy)

: 02/25/2015

Reviewed Date SDS (dd/mm/yyyy)

: 06/02/2019

Revision No.

: 2

Revision Information

: (M)SDS sections updated: All sections modified.

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

HMIS Rating

: * - Chronic hazard 0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe
Health: 1 *Flammability:* 0 *Reactivity:* 0

NFPA Rating

0 - Minimal 1 - Slight 2 - Moderate 3 - Serious 4 - Severe
: *Health:* 1 *Flammability:* 0 *Instability:* 0 *Special Hazards:* None.



Parker Hannifin Corporation - Sporlan Division
206 Lange Drive
Washington, MO, U.S.A., 63090
Telephone: (636) 239 1111

Premium Elastic Sealant Compound

PP22 (P/N 475296)

SDS Revision Date (mm/dd/yyyy): 02/06/2019

Page 10 of 10

SAFETY DATA SHEET

<p><u>Prepared for:</u> Parker Hannifin Corporation - Sporlan Division 206 Lange Drive, Washington, MO 63090 U.S.A. Telephone: (636) 239-1111 www.parker.com Direct all enquiries to: Parker Hannifin Corp. - Sporlan Division.</p>	
<p><u>Prepared by:</u> ICC The Compliance Center Inc. Telephone: (888) 442-9628 (U.S.); (888) 977-4834 (Canada) http://www.thecompliancecenter.com</p>	

DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Parker Hannifin Corporation and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Parker Hannifin Corporation expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Parker Hannifin Corporation.

END OF DOCUMENT