

USA SAFETY DATA SHEET

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

LORD PC11325 Product name: Product Use/Class: **Conductive Coating**

LORD Corporation 111 LORD Drive

Cary, NC 27511-7923 USA

Telephone: 814 868-3180

Non-Transportation Emergency: 814 763-2345 Chemtrec 24 Hr Transportation Emergency No. 800 424-9300 (Outside Continental U.S. 703 527-3887)

EFFECTIVE DATE: 07/13/2021

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATION:

Flammable liquids Category 3

Acute toxicity Inhalation - Dust and Mist Category 4 - 10.0% of the mixture consists of ingredient(s) of unknown toxicity.

Serious eye damage/eye irritation Category 2A

Skin sensitization Category 1

Respiratory sensitization Category 1

Specific target organ systemic toxicity (single exposure) Category 3

Specific target organ systemic toxicity (single exposure) Category 1 Central nervous system, Hematopoietic

System, Kidney, Respiratory system

Specific target organ systemic toxicity (repeated exposure) Category 2 Hematopoietic System, Kidney

Specific target organ systemic toxicity (repeated exposure) Category 1 Respiratory system

Specific target organ systemic toxicity (repeated exposure) Category 1 Eyes, Blood

Aspiration hazard Category 1

Hazardous to the aquatic environment - acute hazard Category 3 Hazardous to the aquatic environment - chronic hazard Category 3

GHS LABEL ELEMENTS:

Symbol(s)







Signal Word

DANGER

Hazard Statements

Flammable liquid and vapor.

Harmful if inhaled.

Causes serious eye irritation.

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

May cause drowsiness or dizziness.

May cause respiratory irritation.

Causes damage to organs.(Central nervous system, Hematopoietic System, Kidney, Respiratory system)

May cause damage to organs through prolonged or repeated exposure. (Hematopoietic System, Kidney)

Causes damage to organs through prolonged or repeated exposure if inhaled.(Respiratory system)

Causes damage to organs through prolonged or repeated exposure. (Eyes, Blood)

May be fatal if swallowed and enters airways.

Product: LORD PC11325, Effective Date: 07/13/2021

Harmful to aquatic life.

Harmful to aquatic life with long lasting effects.

Precautionary Statements

Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Ground/Bond container and receiving equipment.

Use explosion-proof electrical/ventilating/lighting equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/protective clothing/eye protection/face protection.

In case of inadequate ventilation wear respiratory protection.

Do not breathe dust/fume/gas/mist/vapors/spray.

Wash thoroughly after handling.

Do not eat, drink or smoke when using this product.

Use only outdoors or in a well-ventilated area.

Contaminated work clothing should not be allowed out of the workplace.

Avoid release to the environment.

Response

In case of fire: refer to section 5 of SDS for extinguishing media.

Call a POISON CENTER or doctor/physician if you feel unwell.

IF exposed: Call a POISON CENTER or doctor/physician.

Specific treatment (see supplemental first aid instructions on this label).

IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.

If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.

If skin irritation or rash occurs: Get medical advice/attention.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.

Continue rinsing.

IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.

Do NOT induce vomiting.

Wash contaminated clothing before reuse.

Storage

Store in a well-ventilated place. Keep cool.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

Other Hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute: Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea. Dermal absorption possible. Causes skin irritation. Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May be harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

Chronic: Prolonged or repeated contact may result in dermatitis. May cause liver damage. May affect the blood and blood-forming organs. This product contains silver; localized argyria may occur from silver particles imbedded in skin during handling. Repeated exposure to n-butyl acetate caused fetotoxic and developmental effects in laboratory animals. ACGIH considers the glycol ether solvent in this product to be an A3 carcinogen (confirmed animal carcinogen with unknown relevance in humans).

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>Chemical Name</u> <u>CAS Number</u>	Range
--	-------

Product: LORD PC11325. Effective Date: 07/13/2021

Silver	7440-22-4	55 - 60 %
N-Butyl acetate	123-86-4	25 - 30 %
Glycol ether solvent	PROPRIETARY	5 - 10 %
Epoxy novolac resin	PROPRIETARY	5 - 10 %
Diamino diphenyl sulfone	80-08-0	1 - 5 %

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld

4. FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

FIRST AID - SKIN CONTACT: Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

FIRST AID - INHALATION: Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Dry Chemical, Foam, Water Fog UNSUITABLE EXTINGUISHING MEDIA: Not determined for this product.

SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL: Flammable liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid contact. Avoid breathing vapors. Use self-contained breathing equipment.

ENVIRONMENTAL PRECAUTIONS: Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form. Contain and remove with inert absorbent material.

7. HANDLING AND STORAGE

HANDLING: Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

Page: 3

Product: LORD PC11325. Effective Date: 07/13/2021

STORAGE: Do not store or use near heat, sparks, or open flame. Store only in well-ventilated areas. Do not puncture, drag, or slide container. Keep container closed when not in use. Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements.

INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT EXPOSURE LIMIT

<u>Chemical Name</u>	ACGIH TLV- TWA	ACGIH TLV- STEL	OSHA PEL- TWA	OSHA PEL- CEILING	<u>Skin</u>
Silver	0.1 mg/m3	N.E.	0.01 mg/m3	N.E.	N.A.
N-Butyl acetate	150 ppm	200 ppm	710 mg/m3 150 ppm	N.E.	N.A.
Glycol ether solvent	20 ppm	N.E.	N.E.	N.E.	N.A.
Epoxy novolac resin	N.E.	N.E.	N.E.	N.E.	N.A.
Diamino diphenyl sulfone	N.E.	N.E.	N.E.	N.E.	N.A.

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

Engineering controls: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent flammable vapor/air mixtures from accumulating.

PERSONAL PROTECTION MEASURES/EQUIPMENT:

RESPIRATORY PROTECTION: Use a NIOSH approved chemical/mechanical filter respirator designed to remove a combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

SKIN PROTECTION: Use neoprene, nitrile, or rubber gloves to prevent skin contact.

EYE PROTECTION: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

OTHER PROTECTIVE EQUIPMENT: Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

HYGIENIC PRACTICES: Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

ODOR:	Characteristic	VAPOR PRESSURE:	N.D.
APPEARANCE:	Silver	VAPOR DENSITY:	Heavier than Air
PHYSICAL STATE:	Paste	LOWER EXPLOSIVE LIMIT:	0.5 %(V)
FLASH POINT:	84 °F, 28 °C Pensky-	UPPER EXPLOSIVE LIMIT:	8.4 %(V)
	Martens Closed Cup		

BOILING RANGE: 126 - 195 °C EVAPORATION RATE: Slower than n-butylacetate

AUTOIGNITION TEMPERATURE: N.D. DENSITY: 1.91 g/cm3 (15.86 lb/gal)
DECOMPOSITION TEMPERATURE: N.D. VISCOSITY, DYNAMIC: N.D.

ODOR THRESHOLD: N.D. VISCOSITY, KINEMATIC: N.D. SOLUBILITY IN H2O: Insoluble VOLATILE BY WEIGHT: 34.77 % pH: N.A. VOLATILE BY VOLUME: 73.88 %

FREEZE POINT: N.D. VOC CALCULATED: 5.51 lb/gal, 661 g/l

Product: LORD PC11325, Effective Date: 07/13/2021

COEFFICIENT OF WATER/OIL N.D. DISTRIBUTION:

LEGEND: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerization will not occur under normal conditions.

STABILITY: Product is stable under normal storage conditions.

CONDITIONS TO AVOID: High temperatures. Sources of ignition.

INCOMPATIBILITY: Strong acids, bases, and strong oxidizers.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon monoxide, carbon dioxide, Silver fume

11. TOXICOLOGICAL INFORMATION

EXPOSURE PATH: Refer to section 2 of this SDS.

SYMPTOMS: Refer to section 2 of this SDS.

TOXICITY MEASURES:

Chemical Name	<u>LD50/LC50</u>		
Silver	Oral LD50: Rat > 5,000 mg/kg		
	Dermal LD50: Rat > 2,000 mg/kg		
	GHS LC50 (vapour): rat > 55 mg/l /4 h		
N-Butyl acetate	Oral LD50: Rat 10,768 mg/kg		
	Dermal LD50: Rabbit > 17,600 mg/kg		
	Inhalation LC50: Rat 390 ppm/4 h Inhalation LC50: rat 22 mg/l /4 h		
Glycol ether solvent	Oral LD50: Rat 2,400 mg/kg		
	Dermal LD50: Rabbit 1,500 mg/kg		
	Inhalation LC50: Rat >400 ppm/4 h		
Epoxy novolac resin	N.D.		
Diamino diphenyl sulfone	Oral LD50: Rat 1 g/kg		
	Dermal LD50: Rabbit > 4 g/kg		

Germ cell mutagenicity: No classification proposed

Carcinogenicity: No classification proposed

Reproductive toxicity: No classification proposed

12. ECOLOGICAL INFORMATION

ECOTOXICITY:

Chemical Name	Ecotoxicity
Silver	N.D.
N-Butyl acetate	Fish: Lepomis macrochirus 100 mg/l96 h Static Pimephales promelas 17 - 19 mg/l96 h flow-through Plants: Desmodesmus subspicatus 674.7 mg/l72 h
Glycol ether solvent	Fish: Oncorhynchus mykiss 20 - 40 mg/l96 h Invertebrates: Daphnia magna 37 mg/l48 h Plants: Desmodesmus subspicatus > 500 mg/l72 h
Epoxy novolac resin	N.D.
Diamino diphenyl sulfone	Fish: Cyprinus carpio > 100 mg/196 h Static

Page: 5

Product: LORD PC11325, Effective Date: 07/13/2021

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

BIOACCUMULATIVE: Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

14. TRANSPORT INFORMATION

US DOT Road

Proper Shipping Name:PaintHazard Class:3SECONDARY HAZARD:NoneUN/NA Number:1263Packing Group:IIIEmergency Response Guide Number:128

IATA Cargo

PROPER SHIPPING NAME: Paint Hazard Class: 3
HAZARD CLASS: None UN NUMBER: 1263
PACKING GROUP: III
EMS: 3L

<u>IMDG</u>

PROPER SHIPPING NAME: Paint Hazard Class: 3
HAZARD CLASS: None UN NUMBER: 1263
PACKING GROUP: III
EMS: F-E

The listed transportation classification applies to non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS:

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

Chemical Name	CAS Number	Weight % Less Than
Silver	7440-22-4	60.0 %
Glycol ether solvent	PROPRIETARY	10.0 %

TOXIC SUBSTANCES CONTROL ACT:

INVENTORY STATUS

Page: 6

Product: LORD PC11325, Effective Date: 07/13/2021

The chemical substances in this product are on the active TSCA Section 8 Inventory or exempt.

EXPORT NOTIFICATION

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

16. OTHER INFORMATION

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

HMIS RATINGS - HEALTH: 2* FLAMMABILITY: 3 PHYSICAL HAZARD: 0

* - Indicates a chronic hazard; see Section 2

Revision: Section 2, Section 11

Effective Date: 07/13/2021

DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.