

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Product name: **CHEMLOK® 6260**
Product Use/Class: **Adhesive**

LORD Corporation
111 LORD Drive
Cary, NC 27511-7923 USA

Telephone: 814 868-3180
Non-Transportation Emergency: 814 763-2345
Chemtrec 24 Hr Transportation Emergency No.
800 424-9300 (Outside Continental U.S. 703 527-3887)

EFFECTIVE DATE: 11/07/2024

2. HAZARDS IDENTIFICATION**GHS CLASSIFICATION:**

Flammable liquids Category 2
Acute toxicity Dermal Category 4 - 12.9% of the mixture consists of ingredient(s) of unknown toxicity.
Acute toxicity Inhalation - Dust and Mist Category 4 - 9.2% of the mixture consists of ingredient(s) of unknown toxicity.
Skin corrosion/irritation Category 2
Serious eye damage/eye irritation Category 2A
Skin sensitization Category 1
Carcinogenicity Category 2
Reproductive toxicity Category 2
Specific target organ systemic toxicity (single exposure) Category 3
Specific target organ systemic toxicity (single exposure) Category 2 blood system
Specific target organ systemic toxicity (repeated exposure) Category 2 Ears, blood system
Specific target organ systemic toxicity (repeated exposure) Category 1 Nervous System, Respiratory system, Liver
Hazardous to the aquatic environment - acute hazard Category 2
Hazardous to the aquatic environment - chronic hazard Category 2

GHS LABEL ELEMENTS:**Symbol(s)****Signal Word**

DANGER

Hazard statements

Highly flammable liquid and vapor.
Harmful in contact with skin.
Harmful if inhaled.
Causes skin irritation.
Causes serious eye irritation.
May cause an allergic skin reaction.
Suspected of causing cancer.
Suspected of damaging fertility or the unborn child.
May cause harm to breast-fed children.
May cause respiratory irritation.

300001000709

May cause damage to organs.(blood system)
May cause damage to organs through prolonged or repeated exposure.(Ears, blood system)
Causes damage to organs through prolonged or repeated exposure.(Nervous System, Respiratory system, Liver)
Toxic to aquatic life.
Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

Keep away from heat, sparks, open flames, hot surfaces. - No smoking.
Ground, bond container and receiving equipment.
Use explosion-proof electrical, ventilating, lighting equipment.
Use only non-sparking tools.
Take precautionary measures against static discharge.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves, protective clothing, eye protection, face protection.
Use personal protective equipment as required.
Do not breathe dust, fume, mist, vapors, spray.
Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Contaminated work clothing should not be allowed out of the workplace.
Avoid release to the environment.

Response

In case of fire: refer to section 5 of SDS for extinguishing media.
Call a POISON CENTER or doctor, physician if you feel unwell.
Call a POISON CENTER or doctor, physician if exposed or you feel unwell.
Specific treatment (see supplemental first aid instructions on this label).
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
IF ON SKIN (or hair): Remove, take off immediately all contaminated clothing. Rinse skin with water, shower.
If skin irritation or rash occurs: Get medical advice, attention.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
Collect spillage.

Storage

Store in a well-ventilated place. Keep cool.
Store in a well-ventilated place. Keep container tightly closed.
Store locked up.

Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

Other hazards:

This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).

Acute: Vapor harmful; may affect the brain or nervous system causing dizziness, headache or nausea. The imide in this product is a respiratory hazard. Inhalation of product vapors, fumes or particulates during heating should be avoided. In elevated-temperature applications, product may release vapors that may produce cyanosis in the absence of sufficient ventilation or adequate respiratory protection. Possible irritation of the respiratory system can occur causing a variety of symptoms such as dryness of the throat, tightness of the chest, and shortness of breath. May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. This product contains a residual amount of a chemical substance that may cause an allergic skin and/or respiratory reaction. May be harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

Chronic: May affect the gastrointestinal system. The nitrogen substituted aromatic in this product gave positive results for mutagenicity in an Ames Assay study while two other mutagenicity studies proved negative. Ethylbenzene has been classified by IARC as a possible human carcinogen (Group 2B) and reported by NTP to show clear evidence for carcinogenicity in animals. May cause kidney damage.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Hazardous ingredients above the threshold concentration

Chemical Name	CAS Number	Range
Xylene	1330-20-7	55 - 60 %
Ethyl benzene	100-41-4	10 - 15 %
Nitrogen substituted aromatic	PROPRIETARY	5 - 10 %
Zinc oxide (ZnO)	1314-13-2	1 - 5 %
Imide	PROPRIETARY	1 - 5 %
Selenium	7782-49-2	1 - 5 %
Epoxy novalac resin	PROPRIETARY	0.1 - 0.9 %
Toluene	108-88-3	0.1 - 0.9 %
Acetone	67-64-1	0.1 - 0.9 %

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

4. FIRST AID MEASURES

FIRST AID - EYE CONTACT: Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention.

FIRST AID - SKIN CONTACT: Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur.

FIRST AID - INHALATION: Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

FIRST AID - INGESTION: If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

5. FIRE-FIGHTING MEASURES

SUITABLE EXTINGUISHING MEDIA: Cold Fire® fire suppressing agent (see further explanation below)., Water fog, Dry chemical, Foam

UNSUITABLE EXTINGUISHING MEDIA: Carbon Dioxide, Do not use water jet as this may spread the fire.

SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL: Flammable liquid and vapor. Vapours are heavier than air and may spread near ground and travel a considerable distance to a source of ignition and flash back. Keep container tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Dry residues of this component are sensitive to impact and friction. This can result in deflagration. A regular wet clean up of affected surfaces is necessary. Danger of deflagration increases if regular clean up measures are omitted. Please also refer to information given in chapter 7 of this Safety Data Sheet.

WARNING: Due to the combustible nature of the dried film of this product and the potential for smoldering or fire, the accumulation and buildup of the dried film on spray booth walls and floors, spindles, fixtures and other surfaces should be avoided, and any buildup should be removed. Keep the dried film accumulations away from sparks, friction, impact, high heat (>235 F/>112 C) or other sources of ignition. These conditions could cause the dried film to ignite very readily and quickly, and the resulting smoldering or fire may be difficult to extinguish. During removal of accumulation/buildup of this product, take precautions to avoid heat, friction and impact during the cleaning process. Use paint stripper, brass brush, or plastic scraper for cleaning. In the event of smoldering or a fire involving the dried product, Cold Fire®** fire suppressing agent is preferred as the extinguishing medium. If Cold Fire® is not available, use water spray as the extinguishing medium. Take efforts to ensure that these agents reach the base of the smoldering or fire. Parker Lord will not be responsible for personal injuries, property damage or any other damages arising from the accumulation (buildup, cleaning/removal or any related smoldering or fire) resulting from the use of this product. Refer to the Chemlok® Safe Handling Guide for additional information. **NOTE: Parker Lord has determined Cold Fire® fire suppressing agent to be effective in extinguishing fires involving dried Chemlok® adhesives. Parker Lord does not recommend any particular equipment or system for use in delivering or applying Cold Fire® products. Customer is responsible for determining that

Cold Fire® products and any delivery equipment or system is appropriate and effective for customer's specific needs. Use water spray to keep fire exposed containers cool. This product contains a polymeric cross linking agent that depolymerizes at 130°C. In particular at low pressure during vulcanization processes this component can re-deposit as a solid residue on cold surfaces (i. e. equipment parts). Dry residues of this component are sensitive to impact and friction. This can result in deflagration. A regular wet clean up of affected surfaces is necessary. Danger of deflagration increases if regular clean up measures are omitted. Please also refer to information given in chapter 7 of this Safety Data Sheet. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS: Wear full firefighting protective clothing, including self contained breathing apparatus. Water spray may be ineffective. If water is used, fog nozzles are preferable.

6. ACCIDENTAL RELEASE MEASURES

PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT AND EMERGENCY PROCEDURES: Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid breathing vapors. Use self-contained breathing equipment. Avoid contact. See Section 5 for cautionary information on the dried residue of this product.

ENVIRONMENTAL PRECAUTIONS: Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP: Keep non-essential personnel a safe distance away from the spill area. Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid breathing vapors. Use self-contained breathing equipment. Notify appropriate authorities if necessary. Before attempting cleanup, refer to hazard caution information in other sections of this safety data sheet. See Section 5 for cautionary information on the dried residue of this product. Contain and remove with inert absorbent material and non-sparking tools. Avoid contact.

7. HANDLING AND STORAGE

HANDLING: Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored. See Section 5 for cautionary information on handling of the dried residue of this product. Use explosion proof electric equipment.

STORAGE: Do not store or use near heat, sparks, or open flame. Store only in well-ventilated areas. Do not puncture, drag, or slide container. Keep container closed when not in use. Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements.

INCOMPATIBILITY: Strong oxidizers, acids, bases, water.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

COMPONENT EXPOSURE LIMIT

<u>Chemical Name</u>	<u>ACGIH TLV-TWA</u>	<u>ACGIH TLV-STEL</u>	<u>OSHA PEL-TWA</u>	<u>OSHA PEL-CEILING</u>	<u>Skin</u>
Xylene	20 ppm	N.E.	435 mg/m3 100 ppm	N.E.	Not applicable
Ethyl benzene	20 ppm	N.E.	435 mg/m3 100 ppm	N.E.	Not applicable
Nitrogen substituted aromatic	N.E.	N.E.	N.E.	N.E.	Not applicable
Zinc oxide (ZnO)	N.E.	N.E.	5 mg/m3	N.E.	Not applicable
Imide	N.E.	N.E.	N.E.	N.E.	Not applicable
Selenium	0.2 mg/m3	N.E.	N.E.	N.E.	Not applicable

Epoxy novalac resin	N.E.	N.E.	N.E.	N.E.	Not applicable
Toluene	20 ppm	N.E.	200 ppm	300 ppm	Not applicable
Acetone	250 ppm	500 ppm	2,400 mg/m ³ 1,000 ppm	N.E.	Not applicable

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

ENGINEERING CONTROLS: Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent flammable vapor/air mixtures from accumulating.

PERSONAL PROTECTION MEASURES/EQUIPMENT:

Respiratory protection: Use a NIOSH approved chemical/mechanical filter respirator designed to remove a combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

Skin protection: Use neoprene, nitrile, or rubber gloves to prevent skin contact. The most suitable glove should be chosen in consultation with the glove supplier/manufacturer, who can provide information about the breakthrough time of the glove material.

Eye protection: Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

Other protective equipment: Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

Hygienic practices: Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

Odor:	Solvent	Vapor Pressure:	N.D.
Appearance:	Brown	Vapor density:	Heavier than Air
Physical state:	Liquid	Lower explosion limit:	1 %(V)
Flash point:	44 °F, 6 °C Setaflash	Upper explosive limit:	13 %(V)
	Closed Cup		
Boiling range:	136 - 139 °C	Evaporation rate:	Slower than n-butyl-acetate
Autoignition temperature:	N.D.	Density:	1 g/cm ³ (8.30 lb/gal)
Decomposition temperature:	N.D.	Viscosity, dynamic:	≥350 mPa.s @ 25 °C
Odor threshold:	N.D.	Viscosity, kinematic:	≥100 mm ² /s @ 25 °C
Solubility in H₂O:	Insoluble	Volatile by weight:	72.61 %
pH:	N.A.	Volatile by volume:	83.63 %
Freeze point:	N.D.	VOC Calculated:	5.88 lb/gal, 704 g/l
Coefficient of water/oil distribution:	N.D.		

Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Hazardous polymerisation will not occur under normal conditions.

STABILITY: Product is stable under normal storage conditions.

CONDITIONS TO AVOID: High temperatures. Sources of ignition.; For dried product issues, refer to Section 5 of the SDS.

INCOMPATIBILITY: Strong oxidizers, acids, bases, water.

HAZARDOUS DECOMPOSITION PRODUCTS: Decomposition due to high temperatures or a fire causes the formation of irritating and/or toxic gases, organic vapors or fumes., Carbon dioxide, carbon monoxide, chlorine, hydrogen chloride., Oxides of nitrogen, Oxides of selenium, Phosgene, Metal oxides

11. TOXICOLOGICAL INFORMATION

EXPOSURE PATH: Refer to section 2 of this SDS.

SYMPTOMS: Refer to section 2 of this SDS.

TOXICITY MEASURES:

Chemical Name	LD50/LC50
Xylene	Oral LD50: Rat 3,523 mg/kg Dermal LD50: Rabbit 1,100 mg/kg Inhalation LC50: Rat 29.08 mg/l /4 h
Ethyl benzene	Oral LD50: Rat 3,500 mg/kg Dermal LD50: Acute toxicity point estimate 1,100 mg/kg Inhalation LC50: Rat 17.4 mg/l /4 h
Nitrogen substituted aromatic	Oral LD50: rat 1,100 mg/kg
Zinc oxide (ZnO)	Oral LD50: Rat > 5,000 mg/kg Dermal LD50: Rat > 2,000 mg/kg GHS LC50 (vapour): Acute toxicity point estimate 55 mg/l Inhalation LC50: Rat > 5,700 mg/m3 /4 h
Imide	Oral LD50: Rat 1,370 mg/kg GHS LC50 (dust and mist): Rat 0.089 mg/l /4 h
Selenium	Oral LD50: Rat 6,700 mg/kg GHS LC50 (vapour): Acute toxicity point estimate 55 mg/l
Epoxy novalac resin	N.D.
Toluene	Oral LD50: Rat 5,580 mg/kg Dermal LD50: Rabbit > 5,000 mg/kg GHS LC50 (vapour): Rat 25.7 mg/l /4 h
Acetone	Oral LD50: Rat 5,800 mg/kg Dermal LD50: Rabbit > 15,700 mg/kg Inhalation LC50: Rat 50,100 mg/m3 /8 h GHS LC50 (vapour): Rat 76 mg/l /4 h

Germ cell mutagenicity: No classification proposed

Carcinogenicity: Category 2 - Suspected of causing cancer.

Components contributing to classification: Ethyl benzene.

Reproductive toxicity: Category 2 - Suspected of damaging fertility or the unborn child. May cause harm to breast-fed children.

Components contributing to classification: Xylene. Toluene.

12. ECOLOGICAL INFORMATION

ECOTOXICITY:

Chemical Name	Ecotoxicity
Xylene	Fish: Pimephales promelas 13.4 mg/196 h flow-through Lepomis macrochirus 13.1 - 16.5 mg/196 h flow-through Lepomis macrochirus 19 mg/196 h Cyprinus carpio 780 mg/196 h semi-static Oncorhynchus mykiss 2.661 - 4.093 mg/196 h Static Oncorhynchus mykiss 13.5 - 17.3 mg/196 h Lepomis macrochirus 7.711 - 9.591 mg/196 h Static Pimephales promelas 23.53 - 29.97 mg/196 h Static Cyprinus carpio > 780 mg/196 h Poecilia reticulata 30.26 - 40.75 mg/196 h Static <u>Invertebrates:</u> water flea 3.82 mg/148 h Gammarus lacustris 0.6 mg/148 h
Ethyl benzene	<u>Fish:</u> Oncorhynchus mykiss 11.0 - 18.0 mg/196 h Static Oncorhynchus mykiss 4.2 mg/196 h semi-static

	Pimephales promelas 7.55 - 11 mg/196 h flow-through Lepomis macrochirus 32 mg/196 h Static Pimephales promelas 9.1 - 15.6 mg/196 h Static Poecilia reticulata 9.6 mg/196 h Static <u>Plants:</u> Pseudokirchneriella subcapitata 4.6 mg/172 h Pseudokirchneriella subcapitata > 438 mg/196 h
Nitrogen substituted aromatic	N.D.
Zinc oxide (ZnO)	<u>Invertebrates:</u> Daphnia magna 0.04 mg/121 d semi-static
Imide	<u>Invertebrates:</u> Daphnia magna (Water flea) 31.6 mg/148 h
Selenium	<u>Fish:</u> Oncorhynchus mykiss > 100 mg/196 h semi-static <u>Invertebrates:</u> Daphnia magna >= 3.42 µg/121 d semi-static
Epoxy novalac resin	N.D.
Toluene	<u>Fish:</u> Pimephales promelas 12.6 mg/196 h Static Oncorhynchus mykiss 5.89 - 7.81 mg/196 h flow-through Oncorhynchus mykiss 14.1 - 17.16 mg/196 h Static Oncorhynchus mykiss 5.8 mg/196 h semi-static Lepomis macrochirus 11.0 - 15.0 mg/196 h Static Oryzias latipes 54 mg/196 h Static Poecilia reticulata 28.2 mg/196 h semi-static Poecilia reticulata 50.87 - 70.34 mg/196 h Static Morone saxatilis 5.5 mg/196 h <u>Invertebrates:</u> Daphnia magna 11.5 mg/148 h Ceriodaphnia dubia 3.78 mg/148 h <u>Plants:</u> Pseudokirchneriella subcapitata 12.5 mg/172 h Static
Acetone	<u>Fish:</u> Pimephales promelas 6,210 - 8,120 mg/196 h Static Lepomis macrochirus 8,300 mg/196 h Oncorhynchus mykiss 5,540 mg/196 h <u>Invertebrates:</u> Daphnia magna 10,294 - 17,704 mg/148 h Static Daphnia magna 12,600 - 12,700 mg/148 h daphnia pulex 8,800 mg/148 h

PERSISTENCE AND DEGRADABILITY: Not determined for this product.

BIOACCUMULATIVE: Not determined for this product.

MOBILITY IN SOIL: Not determined for this product.

OTHER ADVERSE EFFECTS: Not determined for this product.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility. Waste streams, including the dried adhesive residue, resulting from the use of this product should be tested for RCRA characteristics, including ignitability, to determine any applicable waste classifications.

14. TRANSPORT INFORMATION

US DOT Road

Proper Shipping Name: Adhesives
Hazard Class: 3
Secondary hazard: None
UN/NA Number: 1133
Packing group: II
Emergency Response Guide Number: 128

IATA Cargo

Proper shipping name: Adhesives
Hazard Class: 3
Hazard class: None
UN number: 1133
Packing group: II
EmS: 3L

IMDG

Proper shipping name: Adhesives
Hazard Class: 3
Hazard class: None
UN number: 1133
Packing group: II
EmS: F-E; S-D

The listed transportation classification applies to non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

15. REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS: AS FOLLOWS:

SARA SECTION 313

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Weight percent less than</u>
Xylene	1330-20-7	60.0 %
Ethyl benzene	100-41-4	15.0 %
Zinc oxide (ZnO)	1314-13-2	5.0 %
Selenium	7782-49-2	5.0 %
Toluene	108-88-3	0.9 %

TOXIC SUBSTANCES CONTROL ACT:

INVENTORY STATUS

The chemical substances in this product are on the active TSCA Section 8 Inventory or exempt.

EXPORT NOTIFICATION

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

None

16. OTHER INFORMATION

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

HMIS RATINGS - HEALTH: 2* **FLAMMABILITY:** 3 **PHYSICAL HAZARD:** 0

* - Indicates a chronic hazard; see Section 2

Revision: Section 1, Section 2, Section 3, Section 8, Section 9, Section 11, Section 12, Section 15

Effective Date: 11/07/2024

DISCLAIMER

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.