



Parker Hannifin Corporation -
Sporlan Division
206 Lange Drive
Washington, MO, U.S.A., 63090
Telephone: (636) 239 1111

Retro Fit Test Kit

RTK

SDS Revision Date (mm/dd/yyyy): 10/09/2025

Page 1 of 11

SAFETY DATA SHEET

SECTION 1. IDENTIFICATION

Product identifier used on the label

: **Retro Fit Test Kit**

Other means of identification : RTK (P/N 475363)

Recommended use of the chemical and restrictions on use

: Oil refrigeration test kit
Use pattern: Professional use only
Restriction on use: None known

Chemical family

: Mixture.

Name, address, and telephone number
of the supplier:

Parker Hannifin Corporation - Sporlan Division

206 Lange Drive
Washington, MO, U.S.A.
63090

Supplier's Telephone # : (636) 239-1111

24 Hr. Emergency Tel # : Chemtrec 1-800-424-9300 (Within Continental U.S.); Chemtrec 703-527-3887
(Outside U.S.).

Name, address, and telephone number of
the manufacturer:

Refer to supplier

SECTION 2. HAZARDS IDENTIFICATION

Classification of the chemical

Clear green liquid. Solvent odor.

Most important hazards: Flammable. Toxic in contact with skin or if inhaled. Causes eye irritation. Vapours may cause drowsiness and dizziness. Occupational exposure to the substance or mixture may cause adverse effects. Refer also to TOXICOLOGICAL INFORMATION (Section 11).

This material is classified as hazardous under U.S. OSHA regulations (29CFR 1910.1200) (Hazcom 2012) and Canadian WHMIS regulations (Hazardous Products Regulations) (WHMIS 2015). Classification :

Flammable liquids - Category 2

Acute toxicity, oral - Category 4

Acute toxicity, dermal - Category 3

Acute Toxicity, inhalation - Category 3 (vapor)

Serious eye damage/eye irritation - Category 2A

Reproductive Toxicity - Category 1B

Specific target organ toxicity, single exposure - Category 1

Specific target organ toxicity, single exposure - Category 3 (narcotic effects)

Specific target organ toxicity, single exposure - Category 3 (respiratory)

Physical Hazards Not Otherwise Classified (PHNOC): Not applicable

Health Hazards Not Otherwise Classified (HHNOC): Not applicable

Label elements

Hazard pictogram(s)





Retro Fit Test Kit

SDS Revision Date (mm/dd/yyyy): 10/09/2025

RTK

Page 2 of 11

SAFETY DATA SHEET

Signal Word

DANGER!

Hazard statement(s)

Highly flammable liquid and vapor.
Harmful if swallowed.
Toxic if inhaled.
Toxic in contact with skin.
Causes serious eye irritation.
May cause respiratory irritation.
Suspected of damaging fertility or the unborn child.
Causes damage to organs.
May cause drowsiness or dizziness.

Precautionary statement(s)

Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources - No smoking.
Keep container tightly closed.
Take action to prevent static discharges.
Use non-sparking tools.
Ground/Bond container and receiving equipment.
Wash thoroughly after handling.
Do not breathe vapours or spray mist.
Use only outdoors or in a well-ventilated area.
Do not eat, drink or smoke when using this product.
Wear protective gloves/clothing and eye/face protection.

If exposed or concerned: Call a POISON CENTER or doctor/physician.
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
Call a POISON CENTER or doctor/physician if you feel unwell.
Wash contaminated clothing before reuse.
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.
Continue rinsing.
If eye irritation persists: get medical advice/attention.
If inhaled: Remove person to fresh air and keep comfortable for breathing.
Call a POISON CENTER or doctor/physician if you feel unwell.
If swallowed: Call a poison center/doctor if you feel unwell.
Rinse mouth.
In case of fire: Use water fog, dry chemical, CO₂ or 'alcohol' foam to extinguish.

Store in a well-ventilated place. Keep cool.
Keep container tightly closed.
Store locked up.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Other hazards

Other hazards which do not result in classification:

Burning produces obnoxious and toxic fumes. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be an aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Mixture



Retro Fit Test Kit

RTK

SDS Revision Date (mm/dd/yyyy): 10/09/2025

Page 3 of 11

SAFETY DATA SHEET

<u>Chemical name</u>	<u>Common name and synonyms</u>	<u>CAS #</u>	<u>Concentration (% by weight)</u>
Methanol	Carbinol Methyl hydrate Methyl alcohol	67-56-1	80.0 - 100.0
Acetone	2-Propanone	67-64-1	7.0 - 13.0

The exact concentrations of the above listed chemicals are being withheld as a trade secret.

SECTION 4. FIRST-AID MEASURES

Description of first aid measures

- Ingestion* : Seek immediate medical attention/advice. Do not induce vomiting. Never give anything by mouth to an unconscious person. If vomiting occurs spontaneously, keep victim's head lowered (forward) to reduce the risk of aspiration.
- Inhalation* : Immediately remove person to fresh air. If breathing has stopped, give artificial respiration. If breathing is difficult, give oxygen by qualified medical personnel only. Seek immediate medical attention/advice.
- Skin contact* : Remove/Take off immediately all contaminated clothing. Wash off immediately with plenty of water for at least 15 minutes. Seek immediate medical attention/advice.
- Eye contact* : Immediately flush eyes with running water for at least 20 minutes. Seek immediate medical attention/advice.

Most important symptoms and effects, both acute and delayed

- : Inhalation of methanol vapours may cause substantial visual effects, including irritation, blurred vision, and blindness. CNS depression may result from exposure. May cause headache, nausea, dizziness and other symptoms of central nervous system depression. May result in unconsciousness and possibly death. May cause skin irritation. Symptoms include redness, swelling and sloughing of skin cells (flaking). May be absorbed through the skin, producing symptoms similar to inhalation. May cause severe eye irritation. Methanol is known to cause appreciable eye irritation, and possible blindness. Symptoms may include a burning sensation, pain, watering, and/or changes in vision (blurred vision). Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. May be absorbed through the skin, producing symptoms similar to inhalation. May be an aspiration hazard. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Indication of any immediate medical attention and special treatment needed

- : Immediate medical attention is required. Treat same as methanol poisoning. Symptoms may be delayed.

SECTION 5. FIRE-FIGHTING MEASURES

Extinguishing media

Suitable extinguishing media

- : Dry chemical, foam, carbon dioxide and water fog. Do not use water jet, as this may spread burning material.

Unsuitable extinguishing media

- : Do not use a solid water stream as it may scatter and spread fire.

Special hazards arising from the substance or mixture / Conditions of flammability

- : Highly flammable liquid and vapor. Vapours may ignite explosively. Static discharge, impact, friction, and heat may ignite exposed chemical material. Vapour can travel considerable distance and flashback to a source of ignition. Vapours are heavier than air and may spread along floors. Closed containers may build up pressure when exposed to heat and flame.

Flammability classification (OSHA 29 CFR 1910.106)

- : Flammable liquids - Category 2

Hazardous combustion products

- : Carbon oxides; formaldehyde; irritating fumes and smoke.



Retro Fit Test Kit

SDS Revision Date (mm/dd/yyyy): 10/09/2025

RTK

Page 4 of 11

SAFETY DATA SHEET

Special protective equipment and precautions for firefighters

Protective equipment for fire-fighters

- : Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA. Do not enter without wearing specialized protective equipment suitable for the situation. Firefighter's normal protective clothing (Bunker Gear) will not provide adequate protection. A full-body encapsulating chemical protective suit with positive pressure self-contained breathing apparatus (NIOSH approved or equivalent) may be necessary.

Special fire-fighting procedures

- : Move containers from fire area if safe to do so. Water spray may be useful in cooling equipment exposed to heat and flame.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

- : All persons dealing with the clean-up should wear the appropriate chemically protective equipment. Keep all other personnel upwind and away from the spill/release. Restrict access to area until completion of clean-up. Refer to protective measures listed in sections 7 and 8.

Environmental precautions : Ensure spilled product does not enter drains, sewers, waterways, or confined spaces. For large spills, dike the area to prevent spreading.

Methods and material for containment and cleaning up

- : Remove all sources of ignition. Ventilate area of release. Stop the spill at source if it is safe to do so. Dike for water control. Use only non-sparking tools and equipment in the clean-up process. Contain and absorb spilled liquid with non-combustible, inert absorbent material (e.g. sand), then place absorbent material into a container for later disposal (see Section 13). Notify the appropriate authorities as required.

Special spill response procedures

- : If a spill/release in excess of the EPA reportable quantity is made into the environment, immediately notify the National Response Center in the United States (phone: 1-800-424-8802).
US CERCLA Reportable quantity (RQ): Methanol (5000 lbs / 2270 kg); Acetone (5000 lbs / 2270 kg).

SECTION 7. HANDLING AND STORAGE

Precautions for safe handling

- : Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Use only outdoors or in a well-ventilated area. Wear protective gloves/clothing and eye/face protection. Do not breathe mist/vapors/spray. Keep away from flames and hot surfaces. - No smoking. Take precautionary measures against static discharges. Ground/Bond container and receiving equipment. Use only non-sparking tools. Avoid contact with skin, eyes and clothing. Keep away from heat, sparks and open flames. Use proper bonding and grounding techniques when transferring liquid. Keep away from acids and incompatibles. Always replace cap after use. Wash thoroughly after handling.

Conditions for safe storage : Store locked up. Store in a cool, dry, well-ventilated area. Keep container tightly closed. Store away from incompatibles and out of direct sunlight. Storage area should be clearly identified, clear of obstruction and accessible only to trained and authorized personnel. Inspect periodically for damage or leaks. No smoking in the area.

Incompatible materials : Acids; Strong oxidizing agents.



Retro Fit Test Kit

SDS Revision Date (mm/dd/yyyy): 10/09/2025

RTK

Page 5 of 11

SAFETY DATA SHEET

SECTION 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Limits:				
<u>Chemical Name</u>	<u>ACGIH TLV</u>		<u>OSHA PEL</u>	
	<u>TWA</u>	<u>STEL</u>	<u>PEL</u>	<u>STEL</u>
Methanol	200 ppm (skin)	250 ppm (skin)	200 ppm	N/Av
Acetone	500 ppm	750 ppm	1000 ppm (2400 mg/m ³)	N/Av

Exposure controls

Ventilation and engineering measures

: Use general or local exhaust ventilation to maintain air concentrations below recommended exposure limits.

Respiratory protection

: If the TLV is exceeded, a NIOSH/MSHA-approved respirator is advised. Advice should be sought from respiratory protection specialists. Respirators should be selected based on the form and concentration of contaminants in air, and in accordance with OSHA (29 CFR 1910.134) or CSA Z94.4-02.

Skin protection

: Impervious gloves must be worn when using this product. Advice should be sought from glove suppliers.

Eye / face protection

: Chemical splash goggles are recommended. A full face shield may also be necessary.

Other protective equipment

: Wear resistant clothing and boots. An eyewash station and safety shower should be made available in the immediate working area.

General hygiene considerations

: Handle in accordance with good industrial hygiene and safety practice. Avoid breathing vapour or mist. Avoid contact with skin, eyes and clothing. Wash contaminated clothing before reuse. Wash hands thoroughly after using this product, and before eating, drinking or smoking.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State : Liquid.
Colour : green
Odour : Solvent odor.
Odour threshold : Not available.
pH : 7
Melting Point/Freezing point : -30°C (-22°F)
Initial boiling point and boiling range : 57°C (135°F)
Flash point : -17°C (1.4°F)
Flashpoint (Method) : Seta closed cup
Evaporation rate (BuAe = 1) : > 1
Flammability : Flammable.
Lower explosion or flammability limit (% by vol.) : Not available.
Upper explosion or flammability limit (% by vol.) : Not available.
Oxidizing properties : Not available.
Explosive properties : Not explosive
Vapour pressure : 140 mm Hg



Retro Fit Test Kit

RTK

SDS Revision Date (mm/dd/yyyy): 10/09/2025

Page 6 of 11

SAFETY DATA SHEET

Relative vapour density : 1.1
Relative density / Specific gravity : 0.79
Solubility in water : miscible
Other solubility(ies) : Not available.
Partition coefficient: n-octanol/water or Coefficient of water/oil distribution : Not available.
Auto-ignition temperature : N/Av
Decomposition temperature : Not available
Viscosity : < 2 cps
Particle characteristics : Not applicable.
Volatiles (% by weight) : >99%
Volatile organic Compounds (VOC's) : 711 g/L
Absolute pressure of container : Not applicable.
Flame projection length : Not applicable.
Other physical/chemical comments : Not applicable

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not normally reactive.
Chemical stability : Stable under the recommended storage and handling conditions prescribed.
Possibility of hazardous reactions : No dangerous reaction known under conditions of normal use.
Conditions to avoid : Avoid heat and open flame. Keep away from direct sunlight. Ensure adequate ventilation, especially in confined areas.
Incompatible materials : Acids ;Oxidizers
Hazardous decomposition products : None known, refer to hazardous combustion products in Section 5.

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure:

Routes of entry inhalation : YES
Routes of entry skin & eye : YES
Routes of entry Ingestion : YES
Routes of exposure skin absorption : YES

Potential Health Effects:

Signs and symptoms of short-term (acute) exposure

Sign and symptoms Inhalation

- : Inhalation of methanol vapours may cause substantial visual effects, including irritation, blurred vision, and blindness. CNS depression may result from exposure. May cause headache, nausea, dizziness and other symptoms of central nervous system depression. May result in unconsciousness and possibly death.



Retro Fit Test Kit

SDS Revision Date (mm/dd/yyyy): 10/09/2025

RTK

Page 7 of 11

SAFETY DATA SHEET

Sign and symptoms ingestion

- : May cause gastrointestinal irritation. May cause nausea, vomiting, headache and other central nervous system effects. May be absorbed and cause symptoms similar to those for inhalation. Aspiration into the lungs during swallowing or subsequent vomiting may cause chemical pneumonitis, which can be fatal.

Sign and symptoms skin

- : Direct skin contact may cause slight or mild, transient irritation.

Sign and symptoms eyes

- : Causes serious eye irritation. Symptoms may include redness, pain, tearing and conjunctivitis.

Potential Chronic Health Effects

- : Prolonged or repeated contact may cause drying, cracking and defatting of the skin. May cause central nervous system effects. Inhalation of methanol vapours may cause substantial visual effects, including irritation, blurred vision, and blindness.

Mutagenicity

- : Not expected to be mutagenic in humans.

Carcinogenicity

- : No components are listed as carcinogens by ACGIH, IARC, OSHA or NTP.

Reproductive effects & Teratogenicity

- : Reproductive toxicity - Category 2
Suspected of damaging fertility or the unborn child if inhaled.

Sensitization to material

- : Not expected to be a skin or respiratory sensitizer.

Specific target organ effects

- : Specific target organ toxicity, single exposure - Category 3 (narcotic effects)
Specific target organ toxicity, single exposure - Category 3 (respiratory)
Specific target organ toxicity, single exposure - Category 1
May cause drowsiness or dizziness.
May cause respiratory irritation.
Causes damage to organs.

The substance or mixture is not classified as specific target organ toxicant, repeated exposure.

Medical conditions aggravated by overexposure

- : Not available.

Synergistic materials

- : Not available.

Toxicological data

- : There is no data available for this product.
The calculated ATE values for this mixture are:
ATE oral = 333.00 mg/kg
ATE inhalation (vapours) = 4.55 mg/L
ATE dermal = 436.68 mg/kg

<u>Chemical name</u>	<u>LC₅₀(4hr)</u>	<u>LD₅₀</u>	
	<u>inh, rat</u>	<u>(Oral, rat)</u>	<u>(Rabbit, dermal)</u>
Methanol	> 5000 ppm/6H (4.1 mg/L/4H (vapour))	5628 mg/kg (rat) The estimated human lethal dose is: 300 - 1000 mg/kg	> 393 mg/kg (Monkey) 15 800 mg/kg (rabbit)
Acetone	30 000 ppm (71 mg/L) (vapour)	5800 mg/kg	> 15 800 mg/kg

Other important toxicological hazards

- : CNS depression may result from extreme exposures. Inhalation of methanol vapours may cause substantial visual effects, including irritation, blurred vision, and blindness.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

- : No data is available on the product itself. Do not release, unmonitored, into the environment.



Retro Fit Test Kit

SDS Revision Date (mm/dd/yyyy): 10/09/2025

RTK

Page 8 of 11

SAFETY DATA SHEET

Ecotoxicity data:

<u>Ingredients</u>	CAS #	Toxicity to Fish		
		LC50 / 96h	NOEC / 21 day	M Factor
Methanol	67-56-1	15 400 mg/L (Bluegill sunfish)	N/Av	None.
Acetone	67-64-1	6210 mg/L (Fathead minnow)	N/Av	None.

<u>Ingredients</u>	CAS #	Toxicity to Daphnia		
		EC50 / 48h	NOEC / 21 day	M Factor
Methanol	67-56-1	> 10 000 mg/L (Daphnia magna)	N/Av	None.
Acetone	67-64-1	15 800 mg/L (Daphnia magna)	1660 mg/L	None.

<u>Ingredients</u>	CAS #	Toxicity to Algae		
		EC50 / 96h or 72h	NOEC / 96h or 72h	M Factor
Methanol	67-56-1	22 000 mg/L/96hr (Green algae)	N/Av	None.
Acetone	67-64-1	N/Av	7000 mg/L (Green algae)	None.

Persistence and degradability

: No data is available on the product itself. Methanol is readily biodegradable. Acetone is considered to be readily biodegradable.

Bioaccumulation potential

: No data is available on the product itself.

<u>Components</u>	<u>Partition coefficient n-octanol/water (log Kow)</u>	<u>Bioconcentration factor (BCF)</u>
Methanol (CAS 67-56-1)	-0.74	N/Av
Acetone (CAS 67-64-1)	0.24	0.65

Mobility in soil : No data is available on the product itself.

Other Adverse Environmental effects

: No data is available on the product itself.

SECTION 13. DISPOSAL CONSIDERATIONS

Handling for Disposal

: Handle waste according to recommendations in Section 7. Empty containers retain residue (liquid and/or vapour) and can be dangerous.

Methods of Disposal

: Dispose in accordance with all applicable federal, state, provincial and local regulations.

RCRA

: If this product, as supplied, becomes a waste in the United States, it may meet the criteria of a hazardous waste as defined under RCRA, Title 40 CFR 261. It is the responsibility of the waste generator to determine the proper waste identification and disposal method. For disposal of unused or waste material, check with local, state and federal environmental agencies.



Retro Fit Test Kit








SDS Revision Date (mm/dd/yyyy): 10/09/2025

RTK

Page 9 of 11

SAFETY DATA SHEET

SECTION 14. TRANSPORT INFORMATION

Regulatory Information	UN Number	UN proper shipping name	Transport hazard class(es)	Packing Group	Label
49CFR/DOT	UN1993	Flammable Liquids, n.o.s. (Methanol)	3	II	
49CFR/DOT Additional information	May be shipped as LIMITED QUANTITY when transported in containers no larger than 1.0 Litre, in packages not exceeding 30 kg gross mass.				
TDG	UN1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (Methanol)	3(6.1)	II	 
TDG Additional information	May be shipped as LIMITED QUANTITY when transported in quantities no larger than 1 Litre, in packages not exceeding 30 kg gross mass.				
ICAO/IATA	UN1992	Flammable liquid, toxic, n.o.s. (Methanol)	3(6.1)	II	 
ICAO/IATA Additional information	Refer to ICAO/IATA Packing Instruction				
IMDG	UN1992	FLAMMABLE LIQUID, TOXIC, N.O.S. (Methanol)	3(6.1)	II	 
IMDG Additional information	Consult the IMDG regulations for exceptions. EmS No. F-E,S-D				

Special precautions for user : Appropriate advice on safety must accompany the package. Keep away from heat, sparks and open flame - No smoking.

Environmental hazards : This substance does not meet the criteria for an environmentally hazardous substance according to the IMDG Code. See ECOLOGICAL INFORMATION, Section 12.

SECTION 15 - REGULATORY INFORMATION

US Federal Information:

Components listed below are present on the following U.S. Federal chemical lists:

<u>Ingredients</u>	CAS #	TSCA Inventory	CERCLA Reportable Quantity(RQ) (40 CFR 117.302):	SARA TITLE III: Sec. 302, Extremely Hazardous Substance, 40 CFR 355:	SARA TITLE III: Sec. 313, 40 CFR 372, Specific Toxic Chemical	
					Toxic Chemical	de Minimis Concentration
Methanol	67-56-1	Yes	5000 lbs / 2270 kg	None.	Yes	1%
Acetone	67-64-1	Yes	5000 lb/ 2270 kg	None.	No	N/Ap

SARA TITLE III: Sec. 311 and 312, SDS Requirements, 40 CFR 370 Hazard Classes: Flammable; Acute toxicity; Eye irritation; Specific target organ toxicity, repeated exposure; Reproductive toxicity; Specific target organ toxicity, single exposure.



Retro Fit Test Kit

SDS Revision Date (mm/dd/yyyy): 10/09/2025

RTK

Page 10 of 11

SAFETY DATA SHEET

US State Right to Know Laws:

The following chemicals are specifically listed by individual States:

<u>Ingredients</u>	CAS #	California Proposition 65		State "Right to Know" Lists					
		Listed	Type of Toxicity	CA	MA	MN	NJ	PA	RI
Methanol	67-56-1	Yes	Developmental	Yes	Yes	Yes	Yes	Yes	Yes
Acetone	67-64-1	No	N/Ap	Yes	Yes	Yes	Yes	Yes	Yes

Canadian Information:

Canadian Environmental Protection Act (CEPA) information: All ingredients listed appear on the Domestic Substances List (DSL).

International Information:

Components listed below are present on the following International Inventory list:

<u>Ingredients</u>	CAS #	European EINECs	Australia AICS	Philippines PICCS	Japan ENCS	Korea KECI/KECL	China IECSC	NewZealand IOC
Methanol	67-56-1	200-659-6	Present	Present	(2)-201	KE-23193	Present	HSR001186
Acetone	67-64-1	200-662-2	Present	Present	(2)-542	KE-29367	Present	HSR001070

SECTION 16. OTHER INFORMATION

Legend

: ACGIH: American Conference of Governmental Industrial Hygienists
CAS: Chemical Abstract Services
CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act of 1980
CFR: Code of Federal Regulations
CNS: Central Nervous System
DOT: Department of Transportation
IARC: International Agency for Research on Cancer
LC: Lethal Concentration
LD: Lethal Dose
MSHA: Mine Safety and Health Administration
N/Ap: Not Applicable
N/Av: Not Available
NFPA: National Fire Protection Association
NIOSH: National Institute of Occupational Safety and Health
NTP: National Toxicology Program
OSHA: Occupational Safety and Health Administration
PEL: Permissible exposure limit
SARA: Superfund Amendments and Reauthorization Act
STEL: Short Term Exposure Limit
TDG: Canadian Transportation of Dangerous Goods Act & Regulations
TLV: Threshold Limit Values
TWA: Time Weighted Average



Parker Hannifin Corporation -
Sporlan Division
206 Lange Drive
Washington, MO, U.S.A., 63090
Telephone: (636) 239 1111

Retro Fit Test Kit

RTK

SDS Revision Date (mm/dd/yyyy): 10/09/2025

Page 11 of 11

SAFETY DATA SHEET

References : 1. ACGIH, Threshold Limit Values for Chemical Substances and Physical Agents & Biological Exposure Indices
2. ECHA - European Chemical Agency
3. Canadian Centre for Occupational Health and Safety, CCInfoWeb databases
4. Safety Data Sheets from manufacturer.
5. US EPA Title III List of Lists
6. California Proposition 65 List
7. OECD - The Global Portal to Information on Chemical Substances - eChemPortal

Preparation Date (mm/dd/yyyy)

: 02/07/2019

Reviewed Date SDS (dd/mm/yyyy)

: 09/10/2025

Revision No.

: 3

Revision Information

: All sections modified.

Other special considerations for handling

: Provide adequate information, instruction and training for operators.

Prepared for:

Parker Hannifin Corporation - Sporlan Division
206 Lange Drive, Washington, MO, U.S.A. 63090
Telephone: (636) 239-1111
www.parker.com
Direct all enquiries to: Parker Hannifin Corporation - Sporlan Division.



Prepared by:

ICC The Compliance Center Inc.
Telephone: (888) 442-9628 (U.S.): (888) 977-4834 (Canada)
<http://www.thecompliancescenter.com>



DISCLAIMER

This Safety Data Sheet was prepared by ICC The Compliance Center Inc. using information provided by Parker Hannifin Corporation and CCOHS' Web Information Service. The information in the Safety Data Sheet is offered for your consideration and guidance when exposed to this product. ICC The Compliance Center Inc and Parker Hannifin Corporation expressly disclaim all expressed or implied warranties and assume no responsibilities for the accuracy or completeness of the data contained herein. The data in this SDS does not apply to use with any other product or in any other process.

This Safety Data Sheet may not be changed, or altered in any way without the expressed knowledge and permission of ICC The Compliance Center Inc. and Parker Hannifin Corporation.

END OF DOCUMENT